

SG BODY REFLECTOR BASE SG BODY REFLECTOR MUTING



One active and one passive unit to reduce wiring and installation costs

Robust housing for harsh environments

Easy installation and alignment

Reflective muting arms included in L and T muting version

All advanced features associated to muting function

- 2, 3, 4 beams for body protection
- Controlled heights 500, 800, 900 and 1200 mm
- Up to 8 m operating distance
- Simple configuration through DIP switches
- Integrated muting lamp (muting models)
- Anti-interference coding
- External muting enable signal
- Edged or triggered muting dependent override



SAFETY



APPLICATIONS

- Automatic machines
- Robots
- Automatic assembling lines
- Palletizers and Depalletizers



INDUSTRIES

Food & Beverage, Metalworking, Automotive, Wood, Ceramics

	FINGER	HAND	ARM	BODY
TYPE 2				
TYPE 4				▪

Active unit

SG4-RB2L-050-00-W

TYPE		MUTING ARMS		MONITORED HEIGHT		VERSION	
4	Type 4	---	Linear version: no muting arms included	050	500 mm (2 beams)	E	Base: without integrated muting function
		L	L muting arms included	080	800 mm (3 beams)		
		T	T muting arms included	090	900 mm (4beams)		
				120	1200 mm (4 beams)	W	Muting: with integrated muting function

Passive unit

SG4-RDB2L-090

TYPE		MUTING ARMS		MONITORED HEIGHT	
4	Type 4	---	Linear version: no muting arms included	---	500 mm (2 beams) or 800 mm (3 beams)
		L	L muting arms included	090	900 mm (4 beams)
		T	T muting arms included	120	1200 mm (4 beams)

SG BODY REFLECTOR BASE

SG BODY REFLECTOR MUTING



TECHNICAL DATA

	SG BODY REFLECTOR BASE [SG4-RBx-xxx-00-E] + [SG4-RDBx]	SG BODY REFLECTOR MUTING [SG4-RBx-xxx-00-W] + [SG4-RDBx] [SG4-RBxL/T-xxx-00-W] + [SG4-RDBxL/T]
GENERAL DATA		
Type (EN61496-1)	4	
PL (EN ISO 13849-1)	e	
SIL (IEC 61508)	3	
Resolution	319,75 mm (4 beams) 419,75 mm (3 and 4 beams) 519,75 mm (2 beams)	
Protected height	500 mm (2 beams) 800 mm (3 beams) 900 mm or 1200 (4 beams)	
Operating distance	0.5 ... 8 m 0.5 ... 6.5 m (for SG4-RB4-090-00-E)	0.5 ... 8 m (for SG4-RBx-xxx-00-W) 0.5 ... 6.5 m (for SG4-RB4-090-00-W) 0.5 ... 3 m (for SG4-RBxL/T-00-W)
Retroreflective muting arms operating distance (included in T and L models)		0.5 ... 3 m
Emitter-Receiver muting arms operating distance (not included)	---	0.5 ... 7 m
ELECTRICAL DATA		
Power supply (Vdd)	24 Vdc ± 20%	
Outputs	2 PNP	
Output current	0.5 A max/each output	
Capacitive load	2,2 uF max at 25°C	
Response time	11 ... 12 ms depending on model ^A	
Cables length (for power supply)	70 m max.	
MECHANICAL AND ENVIRONMENTAL DATA		
Operating temperature	0 ...+55 °C	
Humidity	15 ... 95 % (no condensation)	
Mechanical protection	IP 65 (EN 60529)	
FUNCTIONS		
	Manual/Automatic restart	
	External Device Monitoring (EDM)	
	Coding selection with DIP-SW	
	---	T-Muting/L-Muting
		Integrated muting lamp
	---	Muting timeout: 10 min. or ∞
		Integrated muting lamp
	---	Override
	---	Muting enable input
	---	Override status output
	---	Muting filter
	---	Externa muting lamp output

NOTES




^A For detailed informations refer to related Product Datasheet or Manual



SG BODY REFLECTOR BASE

SG BODY REFLECTOR MUTING



CONNECTIONS

	SG BODY REFLECTOR BASE [SG4-RBX-XXX-00-E]	SG BODY REFLECTOR MUTING [SG4-RBX-XXX-00-W] [SG4-RBXL/T-XXX-00-W]
ACTIVE UNIT MAIN CONNECTOR	M12, 8 poles, male 1 = white = RESET/RESTART/RESTART MODE 2 = brown = 24V 3 = green = EDM ENABLE 4 = yellow = EDM 5 = grey = OSSD1 6 = pink = OSSD2 7 = blue = 0V 8 = red = EARTH 	M12, 12 poles, male 1 = brown = 24Vdc 2 = blue = 0 V 3 = white = RESET/RESTART/RESTART MODE 4 = green = OVERRIDE1 5 = pink = OSSD2 6 = yellow = EDM 7 = black = MUTING ENABLE 8 = grey = OSSD1 9 = red = OVERRIDE2 10 = violet = LAMP INPUT 11 = grey-pink = OVERRIDE STATUS 12 = red-blue = EARTH 
ACTIVE UNIT SECONDARY CONNECTOR	--- ---	M12, 5 poles, male 1 = brown = 24Vdc 2 = white = MUTING2 3 = blue = 0V 4 = black = MUTING1 



SG BODY REFLECTOR BASE SG BODY REFLECTOR MUTING



ACCESSORIES

	SG BODY REFLECTOR BASE [SG4-RBX-XXX-00-E] + [SG4-RDBX]	SG BODY REFLECTOR MUTING [SG4-RBX-XXX-00-W] + [SG4-RDBX] [SG4-RBXL/T-XXX-00-W] + [SG4-RDBXL/T]
BRACKETS		
Included with the light curtain	None	
Standard angled brackets (4 pcs)	ST-K4STD-SG-BODY BIG	
Rear fixing bracket mounting (4 pcs)	ST-K4REAR-SG BODY BIG	
Rotating brackets (4 pcs)	ST-K4ROT-SG BODY BIG	
Antivibration support (4 pcs/6 pcs) ^B	ST-K4AV ST-K6AV	
Plastic brackets (4 pcs/6 pcs) ^B	ST-KP4MP ST-KP6MP	
PROTECTION TUBES, STANDS		
IP67/IP69K Tubes	---	
Protective Stands	SG-PSB series ^A	
Stand Plate for SG-PSB	SG-P	
Protective Stands Mounting Brackets (4 pcs/6 pcs) ^B	ST-PS4-SG BODY ST-PS6-SG BODY	
Floor columns	SE-S Series	
SAFETY UNITS		
Safety Unit	SE-SR2	
EDM Relay Box ^C	CS ME-03VU24-Y14	
Safety control unit for single beams and SLC	SG-BWS-T4-MT	
ALIGNMENT TOOL		
LASER Pointer	SG-LP	
ACCESSORIES FOR MUTING		
Muting arms, brackets and cables	---	See page 70
Muting Connection box ^C	---	SG-SRT-1 or SG-SRT-2
External muting lamps	---	LMS Series


NOTES

^A Not possible with T or L muting arms mounted

^B Use 6 brackets for light curtains with length ≥ 1200 mm

^C When using EDM Relay Box or Muting connection boxes, connect EDM input, and be sure EDM function is active on the safety light curtain

SG BODY REFLECTOR BASE - ACTIVE UNIT




MODEL	L1 [mm]	L2 [mm]
SGx-RB2y-050-00-W	609,35	520,5
SGx-RB3y-080-00-W	909,35	820,5
SGx-RB4y-090-00-W	1009,35	920,5
SGx-RB4y-120-00-W	1309,35	1220,5

SG BODY REFLECTOR BASE SG BODY REFLECTOR MUTING




DIMENSIONS

SG BODY REFLECTOR BASE - PASSIVE UNIT ■ SG BODY REFLECTOR MUTING - PASSIVE UNIT



MODEL	L1 [mm]	L2 [mm]
SG4-RDB2	580,5	520,5
SG4-RDB2L	580,5	520,5
SG4-RDB2T	580,5	520,5
SG4-RDB3	880,5	820,5
SG4-RDB3L	880,5	820,5
SG4-RDB3T	880,5	820,5
SG4-RDB4-090	980,5	920,5
SG4-RDB4-120	1280,5	1220,5

SG BODY REFLECTOR BASE WITH T MUTING ARMS - ACTIVE SIDE




SG BODY REFLECTOR BASE SG BODY REFLECTOR MUTING




DIMENSIONS


SG BODY REFLECTOR MUTING WITH T MUTING ARMS - PASSIVE SIDE




SG BODY REFLECTOR MUTING WITH L MUTING ARM
ACTIVE SIDE



PASSIVE SIDE



INDICATORS



SG BODY REFLECTOR BASE SG BODY REFLECTOR MUTING



MODEL SELECTION AND ORDER INFORMATION

SG4 BODY REFLECTOR BASE [SG4-RBX-XXX-00-E]		ORDER NUMBER	SG4 BODY REFLECTOR MUTING [SG4-RBX-XXX-00-W]		ORDER NUMBER
ACTIVE SIDE	SG4-RB2-050-00-E	957951000	LINEAR (WITHOUT MUTING ARMS)		
	SG4-RB3-080-00-E	957951010	SG4-RB2-050-00-W		957951030
	SG4-RB4-090-00-E	957951190	SG4-RB3-080-00-W		957951040
	SG4-RB4-120-00-E	957951020	SG4-RB4-090-00-W		957951180
	---	---	SG4-RB4-120-00-W		957951050
	---	---	WITH T MUTING ARMS		
	---	---	SG4-RB2T-050-00-W		957951080
	---	---	SG4-RB3T-080-00-W		957951090
	---	---	WITH L MUTING ARMS		
	---	---	SG4-RB2L-050-00-W		957951060
	---	---	SG4-RB3L-080-00-W		957951070
PASSIVE SIDE	SG4 BODY REFLECTOR BASE [SG4-RDBX] [SG4-RDBX-XXX]	ORDER CODE	SG4 BODY BIG MUTING [SG4-RDBX] [SG4-RDBXL/T]		ORDER CODE
	SG4-RDB2	957951100	LINEAR (WITHOUT MUTING ARMS)		
	SG4-RDB3	957951110	SG4-RDB2		957951100
	SG4-RDB4-090	957951170	SG4-RDB3		957951110
	SG4-RDB4-120	957951120	SG4-RDB4-090		957951170
	---	---	SG4-RDB4-120		957951120
	---	---	WITH T MUTING ARMS		
	---	---	SG4-RDB2T		957951150
	---	---	SG4-RDB3T		957951160
	---	---	WITH L MUTING ARMS		
	---	---	SG4-RDB2L		957951130
	---	---	SG4-RDB3L		957951140

IMPORTANT NOTES

- 1) Active and passive sides must be ordered separately
- 2) Brackets are not included in the SG4 BODY REFLECTOR packing and must be ordered separately (see accessories table)

CABLES

	ACTIVE UNIT (MAIN CONNECTOR)	LENGTH (m)	ORDER CODE
SG4 BODY REFLECTOR BASE [SG4-RBX-xxx-00-E]	CS-A1-06-U-03	3	95ASE1220
	CS-A1-06-U-05	5	95ASE1230
	CS-A1-06-U-10	10	95ASE1240
	CS-A1-06-U-15	15	95ASE1250
	CS-A1-06-U-25	25	95ASE1260
	CS-A1-06-U-50	50	95A252710
SG4 BODY REFLECTOR MUTING [SG4-RBX-xxx-00-W]	CS-A1-10-U-03	3	95A252720
	CS-A1-10-U-05	5	95A252730
	CS-A1-10-U-10	10	95A252740
	CS-A1-10-U-15	15	95A252750
	CS-A1-10-U-25	25	95A252760
	CS-A1-10-U-50	50	95A252770
	ACTIVE UNIT (SECONDARY CONNECTOR)	LENGTH (m)	ORDER CODE
SG4 BODY REFLECTOR MUTING [SG4-RBX-xxx-00-W]	CS-A1-03-U-03	3	95ASE1170
	CS-A1-03-U-05	5	95ASE1180
	CS-A1-03-U-10	10	95ASE1190
	CS-A1-03-U-15	15	95ASE1200
	CS-A1-03-U-25	25	95ASE1210
	CS-A1-03-U-50	50	95A252700

NOTES

All cables have axial connectors