

CARLO GAVAZZI
Automation Components



Product Overview

Sensors

Photoelectric sensors	4
Capacitive sensors	6
Inductive sensors	7
Ultrasonic sensors	8
Conductive level sensors	9
Magnetic sensors	10
Safety	11
Connectivity	13
Wind sensors	13

Switches

Solid state relays	14
Soft starters	16
Variable frequency drives	17
Industrial relays and Sockets	18
Switching power supplies	19







Controls

Digital panel meters	20
Power analyzers and current transformers	21
Energy analyzers and quick-fit solutions	22
Remote data reading and Data aggregation solutions	23
Building automation	24
Parking guidance system	26
Fieldbuses - Industrial and DuplineSafe	27
Monitoring relays	28
Timers	30

Photoelectric sensors

Carlo Gavazzi offers a wide range of photoelectric sensors designed to be used extensively in applications such as material handling, packaging machinery, automatic door systems, etc. A variety of sensing principles are covered, to fit the requirements of virtually any application: diffuse-reflective (D), background suppression (B), retro-reflective (R) with or without polarization (P), for transparent objects (G), and through-beam (T).

The sensors featuring IP69K ratings and ECOLAB approvals are designed for harsh environments.

Stand alone through beam	M18 PA18	PH18	Miniaturised PD30
			
<ul style="list-style-type: none"> Supply voltage: DC 3-wire Sensing distance: < 20 m Output: NPN/PNP - NO/NC Connectivity: cable or pig-tail Housing: PC, IP67 Features: sensor mute input, T type Approvals: CE - cULus 	<ul style="list-style-type: none"> Supply voltage: DC 4-wire Sensing distance: < 20 m Output: NPN/PNP NO+NC Connectivity: cable or M12 connector Housing: PBTP, IP67, IP68, IP69K Sensor types: D, B, R, P and T Approvals: CE - cULus - ECOLAB 	<ul style="list-style-type: none"> Supply voltage: DC 4-wire Sensing distance: < 20 m Output: NPN/PNP NO+NC Connectivity: cable or M12 connectors Housing: PBTP, IP67, IP68, IP69K Sensor types: D, B, R, P and T Approvals: CE - cULus - ECOLAB 	<ul style="list-style-type: none"> Supply voltage: DC 4-wire Sensing distance: < 15 m Output: NPN/PNP NO+NC Connectivity: cable or M8 connectors Housing: ABS; IP67 Stainless Steel; IP69K Sensor types: D, B, R, P, G and T Approvals: CE - cULus - ECOLAB
PD30 with IO-Link	LD30 with IO-Link and infrared laser	Compact PC50	PM...
			
<ul style="list-style-type: none"> Applications: Pattern Recognition, Speed & Length detection, Divider function, Object and Gap Monitoring Time Delays, Logic Functions Outputs: NPN, PNP, Push-Pull, External inputs Diagnostic function: QoT, QoR, Dust & Temp. Alarm, Operation hours, Power & Detection cycles, Max. and Min. Temp., Short-circuit, Maintenance, No of changes 	<ul style="list-style-type: none"> Background Suppression - Time of flight sensor IO-Link Ver. 1.1 Time delay, ON, OFF, One shot Logic: AND, OR, XOR, Gated SR-FF External input Outputs: NPN, PNP or Push-Pull Diagnostic functions: Operation hours, Power cycles, Detection cycles, Temperatures, Short-circuit, Maintenance 	<ul style="list-style-type: none"> Supply voltage: DC 4-wire, AC/DC 5-wire Sensing distance: < 20 m Output: NPN/PNP - NO+NC, SPDT 3 A Connectivity: cable or M12 connector Housing: ABS/PC, IP67 Sensor types: D, B, R, P and T Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> Supply voltage: AC/DC 5-wire Sensing distance: < 20 m Output: SPDT 3 A Connectivity: cable outlet, terminals Housing: ABS/PC, IP67 Sensor types: D, R, P and T Approvals: CE - UL325 - UL508
Remote amplified sensors MOF...	PA18CL..	EO/ER/EP/ET18 NPB housing	Liquid level VP-sensor
			
<ul style="list-style-type: none"> Supply from system: S142A, B or C Sensing distance: < 50 m Output from system: SPDT 10 A Connectivity: 11 pin socket Housing: syst. PPO, sens. PC IP67 Sensor types: T, ATEX zone 22 Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> Supply voltage: AC 2-wire Sensing distance: < 3 m Output: AC 500 mA Connectivity: cable or M12 connector Housing: PBTP or NPB, IP67 Features: D, R or P type Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> Supply voltage: DC 4-wire Sensing distance: < 20 m Output: NPN/PNP NO+NC Connectivity: cable or M12 connector Housing: NPB, IP67 Sensor types: D, R, P and T Approvals: CE - cULus 	<ul style="list-style-type: none"> Supply voltage: DC 3-wire, AC 2-wire Sensing distance: direct contact Output: NPN/PNP/NO/NC, AC NO/NC Connectivity: cable or M12 connector Housing: PA12, PSU, Glass, NPB, stainless steel, IP67 Approvals: CE - UL - CSA

Photoelectric sensors

Carlo Gavazzi offers a comprehensive range of sensors for Doors, Gates and Entrances, all approved to meet the latest European and North American regulations.

The motion and presence sensors are based on vision technology and have been developed for straight or curved sliding pedestrian doors. They provide easy set-up, easy adjustment of the detection zone and a cross-walk elimination function.

Fork sensor PF74, for lifts	Automatic doors PD98	Automatic doors PD86	Automatic doors PD140
--------------------------------	-------------------------	-------------------------	--------------------------



- Supply voltage: DC 3-wire
- Slot width: < 30 mm
- Output: NPN+PNP NO/NC
- Connectivity: cable outlet
- Housing: PC, IP65
- Features: High dust immunity, T type
- Approvals: CE



- Supply voltage: AC/DC 5-wire
- Sensing distance: < 30 m
- Output: SPDT 1 A
- Connectivity: cable outlet, terminals
- Housing: PC/ABS, IP54
- Features: sensor mute input, T type
- Approvals: CE - UL325



- Supply voltage: AC/DC 5-wire
- Sensing distance: < 20 m
- Output: SPDT 3 A
- Connectivity: cable outlet, terminals
- Housing: PC/ZAMAK, PMMA, IP66
- Features: sensor mute input, T type
- Approvals: CE - UL325 - UL508



- Supply voltage: AC/DC 5-wire
- Sensing distance: < 60 m
- Output: SPST 1 A
- Connectivity: cable outlet, terminals
- Housing: Aluminium/PC, IP65
- Features: sensor mute input, T type
- Approvals: CE - UL325, EN 12445, EN 12453, EN12978, EN/ISO 13849-1 ESPE2

Automatic doors PD180	Long range BGS PD112	Automatic doors wireless safety	Automatic gates wireless safety
--------------------------	-------------------------	------------------------------------	------------------------------------



- Supply voltage: AC/DC 5-wire, battery
- Sensing distance: < 30 m
- Output: SPST 1 A
- Connectivity: cable outlet, terminals
- Housing: PC, IP55
- Features: sensor mute input, T type
- Approvals: CE - UL325, EN 12445, EN 12453, EN12978
- EN/ISO 13849-1 ESPE2



- Supply voltage: DC 4-wire
- Sensing distance: < 2.5 m
- Output: NPN/PNP NO+NC
- Connectivity: cable or M12 connector
- Housing: PC, IP67
- Features: B, industrial or door mode
- Approvals: CE - cULus



- Supply voltage: AC/DC, battery
- Wireless distance: < 10 m
- Output: 3 x SPST, NO 8,2 or NC
- Connectivity: cable outlet, terminals
- Housing: ABS or PC or PA6, IP66/IP67
- Main- and sub-module, 2.4 GHz duplex
- Approvals: CE - cULus - FCC



- Supply voltage: AC/DC, battery
- Wireless distance: < 15 m
- Output: 3 x SPST, NO 8,2 or NC
- Connectivity: cable outlet, terminals
- Housing: ABS or PC or PA6, IP66/IP67
- Main- and sub-module, 2.4 GHz duplex
- Approvals: CE - cULus - FCC

Automatic doors MPF system	Automatic doors PD70	Reflectors	Mounting brackets AMB series
-------------------------------	-------------------------	------------	---------------------------------



- Supply voltage: AC/DC or AC
- Sensing distance: < 15 m
- Output: 2 x SPST 0.5 A or 2 A
- Connectivity: terminals
- System: PC, IP40 sensor: PC+SS, IP67
- Features: sensor mute input, T type
- Approvals: CE - UL325 - UL508 - TÜV



- Supply voltage: DC 3-wire
- Sensing distance: < 12 m
- Output: NPN/PNP - NO/NC
- Connectivity: cable or M8 connector
- Housing: PC, IP67
- Features: sensor mute input, T type
- Approvals: CE - cULus



- High quality retro-reflectors
- Housing shape: square or round
- Round shape: Ø25 to Ø84 mm
- Square shape: 13x17 to 100x100 mm
- Mounting: adhesive or screws
- Material: PMMA/ABS



- Bracket style: Straight or angled
- Sensor size: Ø4, M8, M12, M18 or M30
- Bracket material: galvanized steel or stainless steel AISI316L or Nylon 66 plastic housing
- Adjustability: ±32°
- Head can be rotated 360°













Capacitive sensors

Carlo Gavazzi is renowned for its TRIPLESIELD™ capacitive proximity sensors with outstanding electromagnetic immunity. The 4th Generation TRIPLESIELD™ sensors feature several significant upgrades, including superior electromagnetic immunity and refined sensitivity adjustment with stability indication and are now also available with on-board IO-Link communication. New benefits include a dust and temperature alarm function. Featuring an ECOLAB certified sensor housing rated to IP69K standard, these sensors are exceptionally well suited for a precise detection in environments subject to high temperatures, harsh chemicals, steam and high-pressure cleaning. The sensors are ideal for a wide range of applications that require reliable measurements or monitoring of solid materials or fluids.

<p>M12 Tripleshield™</p> 	<p>M18 and M30 Tripleshield™</p> 	<p>CD34</p> 	<p>CD46 Tripleshield™</p> 
<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 8 mm (F/NF) • Output: NPN/PNP - NO+NC • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: high immunity to EMI • Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> • Supply voltage: AC 2-wire • Sensing distance M18: < 12 mm (F/NF) • Sensing distance M30: < 25 mm (F/NF) • Output: SCR NO+NC • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: high immunity to EMI • Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing: water-based liquids • Output: NPN/PNP NO/NC • Connectivity: cable or M8 4-pin pig-tail • Housing: PBT, IP65, IP66, IP67, IP68, IP69K • Features: automatic tankwall suppression • Approvals: CE - cULus - ECOLAB 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 10 mm (F/NF) • Output: NPN/PNP NO/NC, Teach • Connectivity: cable or M12 pig-tail • Housing: PBT, IP68 • Features: high immunity to EMI • Approvals: CE - UL - CSA
<p>EC55 (VC55) Tripleshield™</p> 	<p>CA18 and CA30 4th Gen. Tripleshield™</p> 	<p>CA18 and CA30 with IO-Link 4th Gen. Tripleshield™</p> 	<p>M18 Chemical resistant</p> 
<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 25 mm (F/NF) • Output: NPN/PNP NO+NC • Connectivity: cable or M12 pig-tail • Housing: PC, IP67 • Features: high immunity to EMI • Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance M18: < 15 mm (F/NF) • Sensing distance M30: < 30 mm (F/NF) • Output: NPN/PNP NO+NC • Connectivity: cable or M12 connector • Housing: PBT, IP67, IP68, IP69K • Features: superior immunity to EMI 	<ul style="list-style-type: none"> • Additional specifications: from standard • IO-Link Ver. 1.1 • Time delay, ON, OFF, One shot • Logic: AND, OR, XOR, Gated SR-FF • External input • Outputs: NPN, PNP or Push-Pull • Diagnostic functions: Operation hours, Power cycles, Detection cycles, Temperatures, Short-circuit, Maintenance 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 12 mm (F/NF) • Output: NPN/PNP NO+NC • Connectivity: cable • Housing: PP or PVC, IP67 • Features: high chemical resistance • Approvals: CE
<p>CD50</p> 	<p>Ø18 ATEX Zone 22</p> 	<p>Ø32 VC11/12</p> 	<p>Ø32 ATEX Zone 20</p> 
<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 10 mm (F) • Output: NPN/PNP NO/NC • Connectivity: cable • Housing: PPE-TPE, IP67 • Approvals: CE 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire, AC 2-wire • Sensing distance: < 12 mm (NF) • Output: NPN/PNP NO+NC, SCR NO/NC • Connectivity: cable • Housing: PBT, IP67 • Features: fixed ON-delay 30 sec • Approvals: CE - UL - CSA - ATEX 	<ul style="list-style-type: none"> • Supply voltage: AC/DC 5-wire, AC 5-wire • Sensing distance: < 20 mm (NF) • Output: SPDT 2 A • Connectivity: cable • Housing: PBT, IP67 • Features: adj. ON or OFF delay 600 sec • Approvals: CE - cULus (M24), ATEX 	<ul style="list-style-type: none"> • Supply voltage: AC/DC 5-wire, AC 5-wire • Sensing distance: < 20 mm (NF) • Output: SPDT 2 A • Connectivity: cable • Housing: PBT, IP67 • Features: adj. ON or OFF delay 600 sec • Approvals: CE - ATEX





Inductive sensors

Carlo Gavazzi offers a broad range of inductive sensors, primarily used for reliable contactless detection of machine moving or rotating parts. These extremely accurate and robust sensors are used in packaging and plastics machines, conveyor systems, agriculture and mobile equipment. They are available in a wide variety of styles, including cylindrical housings (from 4 to 30 mm) with a sensing distance of up to 40 mm, flat pack, and 40 x 40 rotatable head. The ICS E1 series resists to high levels of shock and vibrations, wide temperature variations, voltage peaks of up to 200 V, high pressure and high temperature wash-down thanks to IP69K rating, and have an outstanding immunity to radiated noise of up to 200 V/m. The miniature series, from Ø4 to M8, can reach a frequency of up to 6 kHz and is also available with on-board IO-Link communication, as is the new ICB series, fully embracing the Industry 4.0 requirements.

Ø4	M5	Ø6 - M8	Ø4 - M5 - M8 with IO-Link
			
<ul style="list-style-type: none"> Supply voltage: 3-w DC Sensing distance: ≤ 1.3 mm (F) Output: NPN/PNP - NO/NC Connectivity: cable or M8 connector Housing: stainless steel, IP67 Special features: miniature series, operating frequency up to 6 kHz Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> Supply voltage: 3-w DC Sensing distance: ≤ 1.3 mm (F) Output: NPN/PNP - NO/NC Connectivity: cable or M8 connector Housing: stainless steel, IP67 Special features: miniature series, operating frequency up to 6 kHz Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> Supply voltage: 3-w, 4-w DC (M8) Sensing distance: ≤ 4 mm (F/NF) Output: NPN/PNP - NO/NC Connectivity: cable, M8 connector or M12 connector (M8) Housing: stainless steel, IP67 Special features: miniature series Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> Additional specifications: from standard IO-Link Ver. 1.1 Time delay, ON, OFF, One shot Outputs: configurable NO or NC; NPN, PNP or Push-Pull Switching mode: single point, two point or window Adjustable Sn and hysteresis RPM counter, rotational speed monitoring & temperature alarm
M12	M18	M30	M12 - M18 - M30 with IO-Link
			
<ul style="list-style-type: none"> Supply voltage: 2-w, 3-w, 4-w DC Namur, 2-w AC Sensing distance: ≤ 10 mm (F/QF/NF) Output: NPN/PNP - NO/NC - NO+NC Connectivity: cable or M12 connector Housing: NPB, stainless steel, IP67 Special features: IP68, IP69K and extended temperature range Approvals: CE - UL - CSA - ECOLAB 	<ul style="list-style-type: none"> Supply voltage: 2-w, 3-w, 4-w DC Namur, 2-w AC Sensing distance: ≤ 20 mm (F/QF/NF) Output: NPN/PNP - NO/NC - NO+NC Connectivity: cable or M12 connector Housing: NPB, stainless steel, IP67 Special features: IP68, IP69K and extended temperature range Approvals: CE - UL - CSA - ECOLAB 	<ul style="list-style-type: none"> Supply voltage: 2-w, 3-w, 4-w DC Namur, 2-w AC Sensing distance: ≤ 40 mm (F/NF) Output: NPN/PNP - NO/NC - NO+NC Connectivity: cable or M12 connector Housing: NPB, stainless steel, IP67 Special features: IP68, IP69K and extended temperature range Approvals: CE - UL - CSA - ECOLAB 	<ul style="list-style-type: none"> Additional specifications: from standard IO-Link Ver. 1.1 Time delay, ON, OFF, One shot Outputs: configurable NO or NC; NPN, PNP or Push-Pull Switching mode: single point, two point or window Adjustable Sn and hysteresis RPM counter, rotational speed monitoring & temperature alarm
M12 - M18 - M30 E1	Flat pack	Rotatable head	Loop detector
			
<ul style="list-style-type: none"> Supply voltage: 3-w DC Sensing distance: ≤ 22 mm (F/NF) Output: NPN/PNP - NO/NC Connectivity: cable or M12 connector Housing: stainless steel, IP67, IP68, IP69K Special features: Mobile equipment applications, 8-60 VDC, Load dump protection, 200 V/m radiated immunity Approvals: CE - cULus - E1 	<ul style="list-style-type: none"> Supply voltage: 4-w DC Sensing distance: ≤ 15 mm (F/NF) Output: NPN/PNP - NO+NC Connectivity: cable or plug version Housing: polycarbonate, IP67 Special features: easy mounting and compact dimensions Approvals: CE - UL - CSA 	<ul style="list-style-type: none"> Supply voltage: 2-w AC/DC, 2-w AC, 4-w DC Sensing distance: ≤ 30 mm (F) Output: NPN/PNP - NO/NC - NO+NC Connectivity: terminal block Housing: PBT, IP67 Special features: rotatable head Approvals: CE 	<ul style="list-style-type: none"> Supply voltage: 24-240 VAC/VDC, 12-36 VAC/VDC [LDP] Input: 1 loop or dual loop Output: 2 x SPDT, relay output Mounting: plug [LDP], DIN-rail [LDD] Special features: automatic sensitivity boost, automatic frequency tuning, fail safe/fail secure, advanced diagnostics Approvals: CE - UL [LDP] - CSA [LDP] - cULus [LDD]













Ultrasonic sensors

The ultrasonic sensors from Carlo Gavazzi provide superior sensing solutions for a variety of industrial applications. The UA sensors are excellent for contactless position and distance measurement and are able to detect any sound reflecting targets regardless of colour, transparency or surface. Due to their resistance to temperature variations and immunity against dust, steam and fumes, these sensors are especially well suited to harsh environments. The sensors come in a two switching output version and a combined version with one switching and one analogue output. Thanks to improved technology, an extended sensing distance and a reduced housing length, these sensors provide a state-of-the-art sensor family with high accuracy, versatility and resilience.

M18 Short body PBT housing	M18 Short body stainless steel	M18 Switching output	M18 Analogue output
			
<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: 300 or 800 mm teach-by wire • Output: NPN/PNP - NO/NC • Output: analogue 4-20 mA/0-10 V • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: switching, positive or negative slope • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: 300 or 800 mm teach-by wire • Output: NPN/PNP - NO/NC • Output: analogue 4-20 mA/0-10 V • Connectivity: cable or M12 connector • Housing: AISI316L stainless steel, IP67 • Features: switching, positive or negative slope • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 2.2 m teach-in • Output: NPN/PNP - NO+NC • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: switching • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 2.2 m teach-in • Output: analogue 4-20 mA/0-10 V • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: positive or negative slope • Approvals: CE - cULus
M30 Switching output	M30 Analogue output	M18 Stainless steel	M18 Stainless steel
			
<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 3.5 m teach-in • Output: NPN/PNP - NO+NC, analogue • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: switching • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 2.2 m teach-in • Output: analogue 4-20 mA/0-10 V • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: positive or negative slope • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 2.2 m teach-in • Output: NPN/PNP - NO+NC • Connectivity: cable or M12 connector • Housing: AISI316L stainless steel, IP67 • Features: switching • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 2.2 m teach-in • Output: analogue 4-20 mA/0-10 V • Connectivity: cable or M12 connector • Housing: AISI316L stainless steel, IP67 • Features: positive or negative slope • Approvals: CE - cULus
M30 Stainless steel	M30 Stainless steel	M12 Stainless steel	M30 (Ø39 mm)
			
<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 3.5 m teach-in • Output: NPN/PNP - NO+NC, analogue • Connectivity: cable or M12 connector • Housing: AISI316L stainless steel, IP67 • Features: switching • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 2.2 m teach-in • Output: analogue 4-20 mA/0-10 V • Connectivity: cable or M12 connector • Housing: AISI316L stainless steel, IP67 • Features: positive or negative slope • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 400 mm teach-in • Output: NPN/PNP NO/NC • Connectivity: cable or M12 pig-tail • Housing: stainless steel, IP67 • Features: switching, 4-20 mA/0-10 V • Approvals: CE 	<ul style="list-style-type: none"> • Supply voltage: DC 4-wire • Sensing distance: < 3.5 m teach-in • Output: NPN/PNP - NO+NC, analogue • Connectivity: cable or M12 connector • Housing: PBT, IP67 • Features: switching, 4-20 mA/0-10 V • Approvals: CE - cULus









Conductive level sensors

The Carlo Gavazzi range of conductive level sensors is well suited to most level control applications. The new CL-series of intelligent conductive level controllers is used for conductive liquid level monitoring and pump controlling. CLH models with a flexible conductive level probe can accommodate up to five rods for four different levels of control. Operating levels in the tank can easily be modified by extending or cutting short the length of the electrodes. The typical applications of conductive sensors are level control and flow detection in agriculture, the chemical sector, food and beverage, water distribution and water treatment industries.

CLD 1	CLD 2EB	CLP 2EB	CLP2 Plug-in
			
<ul style="list-style-type: none"> • 5 kΩ to 150 kΩ • Filling or emptying • 17.5 mm width slim housing • ON or OFF delay timer • 1 X 8 A / 250 VAC output 	<ul style="list-style-type: none"> • 250 Ω to 500 kΩ • Filling or emptying • 17.5 mm width slim housing • 24-240 VAC/DC supply • 1 X 8 A / 250 VAC output 	<ul style="list-style-type: none"> • 5 kΩ to 150 kΩ • Filling or emptying • 35.5 mm width housing • Simple amplifier • 1 X 8 A / 250 VAC output 	<ul style="list-style-type: none"> • 250 Ω to 500 kΩ • Filling or emptying • 35.5 mm width housing • 3 conductive ranges (L/S/H) • 2 X 8 A / 250 VAC output
CLD2 DIN-rail	CLP2 Master-Slave	CLP4 Plug-in	CLD4 DIN-rail
			
<ul style="list-style-type: none"> • 250 Ω to 500 kΩ • Filling or emptying • 35.5 mm width housing • 3 conductive ranges (L/S/H) • 2 X 8 A / 250 VAC output 	<ul style="list-style-type: none"> • 250 Ω to 500 kΩ • Filling or emptying • Cascade up to 7 amplifiers • Many different levels • 1 X 8 A / 250 VAC output 	<ul style="list-style-type: none"> • 250 Ω to 500 kΩ • Many different functions • Up to 4 levels • Tank well function • 2 X 8 A / 250 VAC output 	<ul style="list-style-type: none"> • 250 Ω to 500 kΩ • Many different functions • Up to 4 levels • Tank well function • 2 X 8 A / 250 VAC output
CLH	VN/VT	VH	A94-10
			
<ul style="list-style-type: none"> • 3 or 5 electrodes • Standard 1 m length • Length can be extended • Electrode isolation • Flexibility 	<ul style="list-style-type: none"> • Up to 4 electrodes • Standard 1 m length • Stainless steel electrodes • Electrode isolation • Different housing materials 	<ul style="list-style-type: none"> • 1 electrode • Level hanging probe • UV resistant PVC or Neoprene cable • Stainless steel electrodes • Suitable for swimming pools 	<ul style="list-style-type: none"> • 2 electrodes • Level hanging probe • 5 m PVC cable • Polyester housing • Suitable for swimming pools

Magnetic sensors

Carlo Gavazzi offers a comprehensive range of proximity magnetic sensors to be used in detection applications. They are employed in conjunction with an external magnet: when the sensor approaches the magnet, the output from the sensor changes the status. There is a wide variety of styles available including rectangular, cylindrical and slotted. Safety magnetic sensors with special coded magnets are available in compact or standard rectangular housings, the ideal solution to monitor sliding, hinged and removable safety guards. Magnetic sensors are frequently used for elevators and lifts, gate control, level detection and access control. Some proximity and level sensors are certified for use in explosive environments (ATEX).

Ø 6	Ø 13,5	M8	M10
			
<ul style="list-style-type: none"> • Max. switch. power contact: 10 VA • Operating distance: > 8 mm • Output: NO • Connectivity: 0.5 m twin lead cable • Housing: plastic, IP67 • Special features: cylindrical series • Approvals: CE 	<ul style="list-style-type: none"> • Max. switch. power contact: up to 120 VA • Operating distance: 3 - 12 mm • Output: NO, NC, CO • Connectivity: 0.5 m PVC cable • Housing: plastic, IP67 • Special feature: cylindrical series • Approvals: CE 	<ul style="list-style-type: none"> • Max. switch. power contact: up to 10 VA • Operating distance: 8 - 28 mm • Output: NO, CO • Connectivity: 2 m PVC cable • Housing: stainless steel or NPB, IP67 • Special feature: cylindrical series • Approvals: CE 	<ul style="list-style-type: none"> • Max. switch. power contact: up to 120 VA • Operating distance: 7 - 36 mm • Output: NO, CO • Connectivity: 2 m PVC cable • Housing: brass or NPB, IP67 • Special feature: cylindrical series • Approvals: CE
M12	M16	Flat type	Level (inox)
			
<ul style="list-style-type: none"> • Max. switch. power contact: up to 120 VA • Operating distance: 2 - 20 mm • Output: NO, NC, CO, bistable • Connectivity: 2 m PVC cable or 2 m silicone cable • Housing: brass, NPB, plastic, IP67 • Special feature: includes a special family for elevators • Approvals: CE 	<ul style="list-style-type: none"> • Max. switch. power contact: up to 100 VA • Operating distance: 5 - 32 mm • Output: CO, Bistable • Connectivity: 2 m PVC cable or 0.5 m silicone cable • Housing: brass, plastic, IP67 • Special features: includes a special family up to 150°C • Approvals: CE 	<ul style="list-style-type: none"> • Max. switch. power contact: up to 120 VA • Operating distance: 5 - 40 mm • Output: NO, NC, CO, bistable • Connectivity: PVC cable, pig tail, twin lead cable • Housing: plastic, IP67 • Special features: includes a family with 2xNC outputs • Approvals: CE 	<ul style="list-style-type: none"> • Max. switch. power contact: up to 120 VA • Float diameter: Ø 28, Ø 53 • Output: NO, NC, CO, NO/NC • Connectivity: silicone cable, XLPE cable • Housing: stainless steel, IP67, IP68 • Special feature: includes a family up to 200°C • Approvals: CE
Level (plastic)	ATEX	Safety sensors (standard)	Safety sensors (compact)
			
<ul style="list-style-type: none"> • Max. switch. power contact: up to 120 VA • Float diameter: Ø 25, 17.5, 31, 44, 45 mm • Output: NO, CO, NO/NC • Connectivity: PVC cable, silicone cable, XLPE cable • Housing: plastic, IP67, IP68 • Special feature: possibility to reverse the output function • Approvals: CE 	<ul style="list-style-type: none"> • Max. switch. power contact: up to 100 VA • Operating distance: 8 - 35 mm • Output: NO, NC, CO • Connectivity: silicone, HF PUR, PVC cable • Housing: stainless steel, self-ext. plastic, IP66, IP67 • Special features: Category 2G, 2D or 1G, 1D • Approvals: CE - TUV Sud 	<ul style="list-style-type: none"> • Max. switch. power contact: 6 W • Operating distance (Sao): 5 mm, 8 mm, 18 mm depending on actuator • Output: 2 NO, 1 NO + 1 NC, 2 NO + 1 NC • Connectivity: PVC cable, M8-plug, pig-tail with M12 connector • Housing: rectangular, plastic, IP67, IP69K [Plug version without LED] • Approvals: CE - cULus 	<ul style="list-style-type: none"> • Max. switch. power contact: 6 W • Operating distance (Sao): 5 mm • Output: 2 NO, 1 NO + 1 NC, 2 NO + 1 NC • Connectivity: PVC cable, M8-plug • Housing: rectangular, plastic, IP67, IP69K [Plug version without LED] • Special features: compact dimensions, left or right exit, with or without LED • Approvals: CE - cULus

Safety

Carlo Gavazzi's range of safety modules includes modules for light curtains, safety mats, two hand control (anti-tie down devices), magnetic and safety switches and emergency stops. They are suitable for use in applications up to Performance Level "e" and Safety Integrity Level SIL 3. We also offer extension units which can be used to increase the number of safety outputs. Our safety modules are cUL and TUV approved.

Our modules are powered by 24 VAC/DC and feature LED status indicators.

SMS20/SMS31 Emergency stop	SMSA31 Safety gates	SM2H21 Two hand control	SMS20 Lift levelling
-------------------------------	------------------------	----------------------------	-------------------------



- Emergency stop and safety gate modules up to Performance Level "e" for category 0 emergency stops
- 2 NO safety outputs (SMS20) or 3 NO safety outputs plus 1 NC auxiliary (SMS31) with automatic, manual and monitored manual start
- Detachable screw terminals



- Safety gate modules, with antivalent function, up to Performance Level "e" for safety magnetic switches
- 3 NO safety outputs plus 1 NC auxiliary with automatic, manual and monitored manual start
- Detachable screw terminals



- Safety module, up to Performance Level "e", for Two-hand controls Type IIIC (EN 574)
- For high risk applications such as presses and punches
- Detachable screw terminals



- Designed to be used in lift plants for floor levelling of the cabin.
- Compliant with standards EN 81-20, EN 81-50
- 2 NO safety outputs
- Detachable screw terminals

SME41 Expansion modules	Multifunction module delayed outputs	Multifunction modules instantaneous outputs	Lift levelling safety module
----------------------------	---	--	---------------------------------



- The expansion module is used to increase the number of safety outputs, up to Performance Level "e"
- 4 NO instantaneous relay outputs plus 1 NC auxiliary output for feedback
- Detachable screw terminals



- The device can be connected with different types of input: E-stop, E-gate, limit switch, non-contact switch, safety light curtains (ESPE Type 4, Type 2), safety light beam (single beam), safety mat
- 2 x OSSD direct + 2 x OSSD delayed
- Selectable delay time. Can be easily set-up through the hex-switch, from 0 to 30 sec.



- The device can be connected with different types of input: E-stop, E-gate, limit switch, non-contact switch, safety light curtains (ESPE Type 4, Type 2), safety light beam (single beam), safety mat
- 3 x OSSD (NO) + 1 OSSD Auxiliary (1 NC) (CM30D1A) or 4 x OSSD (NO) (CM40DDA)
- 4 LEDs on the front panel indicate the status and any errors during operation



- Control of levelling, re-levelling and preliminary operation with doors not closed and locked
- 2 x OSSD Safety (NO) + 2 OSSD Auxiliary (1 NC and 1 NO)
- Possibility of connecting mechanical or magnetic switches (reed contact)

NLG Light curtains	Configurable master module	Speed monitoring modules	I/O Expansion modules
-----------------------	-------------------------------	-----------------------------	--------------------------



- Control Electro Sensitive Protective Equipment (ESPE) with static PNP or relay outputs reaching Performance Level "e"
- 2 NO safety outputs (NLG02) or 3 NO safety outputs plus 1 NC auxiliary (NLG13) with automatic/manual or monitored manual reset version
- Fixed or detachable screw terminals



- Configurable Master safety controller
- Simultaneous monitoring of several safety devices and commands
- 8 digital safety inputs
- 2 OSSD digital safety output pairs
- 4 Test outputs and 2 programmable status outputs and separate EDM and Start/Restart



- The modules allow the configuration of up to 4 speed thresholds for each logic output (axis)
- Each module integrates two logic outputs configurable via the MSD and is therefore capable of controlling up to two independent axes
- RJ45 for encoder connections and terminal blocks for connection of proximity (up to 2 proximity per module)



- I/O module: 8I + 20 + 4 test outputs and 2 programmable status outputs
- I + Test 0 module: 12I + 8TO and separate EDM and Start/Restart
- Input only modules: 8/16 safety inputs + 4 test 0
- Output only modules: 2/4 OSSD and separate EDM and Start/Restart
- Relay Output modules: different versions with NO and NC configurations

Safety

Carlo Gavazzi offers a complete range of limit and safety switches, providing machine manufacturers and panel builders with global and exhaustive solutions which allow machinery to operate correctly, minimizing process stops and personnel risk. Switches may be operated by process variables such as pressure, temperature, flow, current, voltage and force, acting as sensors in a process and used to automatically control a system.

<p>PS21L 30 mm series</p>	<p>PS31L 40 mm series</p>	<p>PS42L 50 mm series</p>	<p>PS43L 60 mm series</p>
			
<ul style="list-style-type: none"> • Plastic or Metal housing • 1 NO + 1 NC, 2 NO or 2 NC contacts, snap or slow action • Selectable actuator type • Selectable cable gland or pre-wired M12 plug connection • IP65 or IP66 degree of protection 	<ul style="list-style-type: none"> • Plastic or Metal housing • 1 NO + 1 NC, 1 NO + 2 NC, 2 NO + 1 NC, 2 NO, 2 NC, 3 NO or 3 NC contacts, snap or slow action • Selectable actuator type • Selectable cable gland or pre-wired M12 plug connection • IP65 or IP66 degree of protection 	<ul style="list-style-type: none"> • Plastic or Metal housing • 1 NO + 1 NC, 2 NO or 2 NC contacts, snap or slow action • Selectable actuator type • Selectable cable gland connection • IP65 or IP66 degree of protection 	<ul style="list-style-type: none"> • Metal housing • 1 NO + 1 NC, 1 NO + 2 NC, 2 NO + 1 NC, 2 NO, 2 NC, 3 NO or 3 NC contacts, snap or slow action • Selectable actuator type • Selectable cable gland connection • IP65 or IP66 degree of protection
<p>PS21M/PS31M prewired series</p>	<p>PS21K with manual reset</p>	<p>PS38H Safety hinge</p>	<p>ESI Safety Interlock</p>
			
<ul style="list-style-type: none"> • Plastic or Metal housing • 1 NO + 1 NC, snap or slow action • Selectable actuator type • Prewired 1m PVC cable • IP67 degree of protection 	<ul style="list-style-type: none"> • Plastic or Metal housing • 1 NO + 1 NC or 2 NC contacts, snap or slow action • Selectable actuator type • Selectable cable gland connection • IP65 or IP66 degree of protection 	<ul style="list-style-type: none"> • Plastic housing • 2 NO + 2 NC or 1 NO + 3 NC contacts, snap or slow action • Interlock type 1 as per EN14119 • M12 plug or cable connection • IP67 degree of protection 	<ul style="list-style-type: none"> • Plastic housing • 1 NO + 1 NC (coil) + 1 NC (actuator), 1 NO + 1 NC (coil) + 1 NO (actuator), 2 NC (coil) + 1 NO + 1 NC (actuator) • Interlock type 2 as per EN14119 • Adjustable head for key actuator • IP65 degree of protection
<p>PS21S/31S/42S/43S actuated by key</p>	<p>PS21R/31R/42R/43R actuated by pull wire</p>	<p>PS21H-HC actuated by hinge</p>	<p>PS21H-HZ actuated by hinge</p>
			
<ul style="list-style-type: none"> • Plastic or Metal housing • 1 NO + 1 NC, 1 NO + 2 NC, 2 NO + 1 NC, 2 NO, 2 NC, 3 NO or 3 NC contacts, snap or slow action • Selectable actuating key; optional adjustable key • Selectable cable gland connection • IP65 or IP66 degree of protection 	<ul style="list-style-type: none"> • Metal housing • 1 NO + 1 NC, 1 NO + 2 NC, 2 NO + 1 NC, 2 NO, 2 NC, 3 NO or 3 NC contacts, snap or slow action • Manual or automatic reset • Selectable cable gland connection • IP66 degree of protection 	<ul style="list-style-type: none"> • Plastic housing • 1 NO + 1 NC, 2 NO or 2 NC contacts, snap or slow action • Operated by hinge • Selectable cable gland connection • IP65 degree of protection 	<ul style="list-style-type: none"> • Plastic housing • 1 NO + 1 NC, 2 NO or 2 NC contacts, snap or slow action • Operated by hinged shaft • Selectable cable gland connection • IP65 degree of protection

Connectivity and Wind sensors

To support its wide range of sensors, Carlo Gavazzi also offers a number of accessories and connectors for all market needs, that are characterized by high quality standards. The SCTL55 is the Industry 4.0 portable and user-friendly configurator for IO-Link sensors, providing simple configuration, monitoring and advanced diagnostic data. Y-series IO-Link masters allow connection of up to 8 smart devices to the higher-level control system and support EtherNet/IP™, PROFINET IO, and MODBUS TCP. Thanks to the integrated web server and IODD interpreter it is easy to configure and access diagnostic information via a web browser, also remotely from PC or tablets. Wind sensors are designed for measuring wind direction and wind speed in a wide variety of applications including wind turbines, cranes, weather stations and solar panels.

Y-Series IO-Link masters	SCTL55 Smart configurator	ST03 Sensor tester	CONE1 Straight and Angled
-----------------------------	------------------------------	-----------------------	------------------------------



- DIN rail or Machine mount fieldbus module
- IO-Link v1.1 and v1.0
- Integrated web server accessible via browser
- 8 IO-Link outputs, 2 Ethernet ports
- EtherNet/IP™ or PROFINET IO, Modbus TCP
- OPC UA support
- Approvals: CE - UL - FCC



- Handheld device for easy monitoring, diagnostics and configuration of IO-Link sensors
- IO-Link v1.1
- 5.5" HD touch screen display
- Automatic IODD file download via Wi-Fi
- High capacity rechargeable battery
- M8 3-wire, M8 4-wire and M12 connectors
- Approvals: CE - FCC - IC



- Sensor tester
- Suitable for 2/3/4 wire and NAMUR sensor
- LED shows NO or NC
- LED shows NPN or PNP
- Comes with buzzer



- M12 connector
- Straight version [-S..]
- Angled version [-A..]
- 2/5 m cable length
- 3/4/5 wire DC version
- UL approval
- IP67 rating
- PVC cable or PUR cable on request

CONE5 Straight and Angled	CONB1..W Straight and Angled	CONH6 Straight and Angled	CONE14NF-S/-A Connector only
------------------------------	---------------------------------	------------------------------	---------------------------------



- M8 connector
- Straight version [-S..]
- Angled version [-A..]
- 2/5 m cable length
- 3 or 4 wire DC version
- UL approval
- IP67 rating
- PVC cable or PUR cable on request



- M12 connector
- Straight version [-S.W]
- Angled version [-A.W]
- 2 or 5 m cable length
- 4 wire DC version
- UL Ecolab approval
- IP69K rating
- TPE cable



- M12 connector
- Straight version [-S..]
- Angled version [-A..]
- 2 or 5 m cable length
- 2 wire AC version
- IP67 rating
- PVC cable



- M12 connector only
- Straight version [CONE14NF-S]
- Angled version [CONE14NF-A]
- Field-wireable
- 4 wire version
- IP67 rating

DWS-V Wind speed	DWS-V-AGP Wind speed	DWS-D Wind direction
---------------------	-------------------------	-------------------------



- Anemometer
- Measures wind speed
- 2 to 30 m/s
- PNP or NPN output
- PVC cable connection
- -20°C to +60°C
- IP54 rating
- Built-in heater, High ESD protection



- Anemometer, 4-20 mA output
- Measures wind speed
- 2 to 50 m/s
- PNP or NPN output
- M16 plug
- -20°C to +60°C
- IP54 rating
- Built-in heater, High ESD protection



- Wind vane
- Measures wind direction
- 0° to 360° measurement
- 90° measurement interval
- PNP or NPN output
- -20°C to +60°C
- IP54 rating
- Built-in heater, High ESD protection

Solid state relays

Carlo Gavazzi offers a comprehensive range of solid state relays (SSRs) covering AC and DC switching, 1-phase and 3-phase, suited for a wide range of applications. SSRs are used extensively in the plastics, packaging, food processing, semiconductor manufacturing and HVAC industries primarily for temperature control. Thanks to their fast switching capability, SSRs are the most reliable switching components for process accuracy. Over the years, SSRs have become the preferred switching solution compared to mechanical contactors as they can perform a very large number of switching cycles without breaking down. This ensures low machine downtime and hence lower running costs.

PCB mounting RP1A, RP1D



- AC or DC output switching
- Zero Cross [RP1A], Instant On [RP1B] or DC [RP1D]
- Ratings up to 480 VAC, 5.5 AAC [RP1A/B]
- Ratings 350 VDC / 1 ADC, 60 VDC / 8 ADC [RP1D]
- Approvals: CE - cURus - VDE - [RP1A/B] - EAC - UKCA

1-phase SSR RF1



- Zero Cross [RF1A] or Instant On [RF1B] switching
- Ratings up to 280 VAC, 25 AAC
- Integrated transistor for output protection
- Control ON LED
- Approvals: CE - UR - CSA - VDE - EAC - UKCA

1-phase SSR RA



- Zero Cross output switching
- Ratings up to 660 VAC, 110 AAC, 18000 A²s
- High blocking voltage option
- Control ON LED
- Approvals: CE - UR - CSA - EAC - UKCA

1-phase SSR RM1, RAM1



- Zero Cross [RM1A] or Instant On [RM1B] switching
- Ratings up to 759 VAC, 125 AAC, 18000 A²s
- Integrated varistor for output protection
- Control ON LED
- Approvals: CE - UR - CSA - CCC - EAC - UKCA - VDE [RAM1]

2- pole SSR RA2A



- 2 poles in 1 housing, independent control
- Ratings up to 660 VAC, 40 AAC per pole
- Zero Cross switching
- DC control voltage
- Approvals: CE - UR - EAC - UKCA - CSA (excl. RA2A..C)

2- pole SSR RKD2, RK2



- 2 poles in 1 housing, independent control [RKD2] or common control [RK2]
- Ratings up to 660 VAC, 75 AAC per pole, 9800 A²s
- Zero Cross or Instant On switching
- DC control voltage
- Approvals: CE - UR - CSA - VDE - EAC - UKCA

3-phase SSR RZ3A



- 3-phase Zero Cross switching
- Suitable for resistive and inductive loads
- Ratings up to 759 VAC, 75 AAC
- Control ON LED
- Approvals: CE - UR - CSA (excl. 690 VAC) - EAC - UKCA

DC SSR RM1D



- DC switching
- Ratings up to 100 A / 60 VDC, up to 50 A / 200 VDC, up to 10 A / 500 VDC
- DC control voltage
- Control ON LED
- Approvals: CE - UR - CSA - EAC - UKCA

Slim line SSR RGS1



- Compact, 17.5 mm wide
- Zero Cross [RGS1A] or Instant On [RGS1B] switching
- Ratings up to 759 VAC, 90 AAC, 18000 A²s
- AC or DC control
- Approvals: CE - UR - CSA - VDE - EAC - UKCA - GL (50 AAC only)

Slim line SS contactors RGC1



- Min. product width 17.5 mm (37 AAC) up to 70 mm (85 AAC)
- Ratings up to 660 VAC, 85 AAC, 18000 A²s
- E-type (contactor) or U-type (SSR) terminal layout
- 100 kA UL short circuit current rating
- Approvals: CE - cULus - VDE - EAC - UKCA - GL (up to 30 AAC)

Slim line SS contactors RGH1



- Zero Cross switching, Blocking voltage up to 1600 Vp
- Ratings up to 759 VAC, 65 AAC, 6600 A²s
- Integrated varistor on output (up to 660 VAC)
- 100 kA UL short circuit current rating
- Approvals: CE - cULus - VDE - EAC - UKCA

3-phase SS contactors RGC2A, RGC3A















- 3-pole [RGC3A] or 2-pole switching + 1 direct pole [RGC2A]
- Ratings up to 660 VAC, 75/65 AAC [RGC2/3]
- Motor ratings up to 11 kW/ 15 HP @ 400 VAC
- RGC.M for system malfunction monitoring
- Approvals: CE - cULus - EAC - CCC - UKCA - VDE [RGC..10]

Solid state relays

Carlo Gavazzi now offers additional features to the switching function of the SSR. Integrated monitoring of loads or SSR malfunction ensures a timely failure detection and so scrap and rework costs in production plants are kept to a minimum. SSRs with a communication interface embrace Industry 4.0. Data is accessible from SSRs in real time and can be used to predict machine abnormalities in a timely manner to avoid stoppages.

Carlo Gavazzi also offers a range of accessories that complement the solid state relay solutions, such as heatsinks, terminal adaptors, protection covers and thermal interfaces. Carlo Gavazzi's SSRs conform to international standards.

Proportional controllers RM1E	Proportional controllers RGS1P	Proportional controllers RGC1P	Proportional controllers RGC2P, RGC3P
			
<ul style="list-style-type: none"> • Phase angle switching • Ratings up to 660 VAC, 125 AAC, 18000 A²s • 4-20 mA or 0-10 VDC analogue input • Integrated varistor for output protection • Approvals: CE - UR - CSA - EAC - UKCA 	<ul style="list-style-type: none"> • Selectable switching mode - Phase angle, full cycle, advanced full cycle switching or soft start • 4-20 mA or 0-10/0-5/1-5 V input • Ratings up to 660 VAC, 90 AAC • Integrated varistor for output protection • Approvals: CE - UR - CSA - EAC - UKCA 	<ul style="list-style-type: none"> • Selectable switching mode - Phase angle, full cycle, advanced full cycle switching or soft start • 4-20 mA or 0-10/0-5/1-5 V input • Ratings up to 660 VAC, 63 AAC • Integrated varistor for output protection • Approvals: CE - cULus - EAC - UKCA 	<ul style="list-style-type: none"> • Phase angle, full cycle, advanced full cycle switching or soft start • 0-20/4-20/12-20 mA or 0-10/0-5/1-5 V input • RGC2P ratings (2-phase): 660 VAC, 75 AAC/pole • RGC3P ratings (3-phase): 660 VAC, 65 AAC/pole • Integrated monitoring for load loss or SSR malfunction • Approvals: CE - cULus - EAC - CCC - UKCA
System monitoring RA..S	System monitoring RGS..M, RGC..M	Current sensing RGS1S, RGC1S	Communication interface NRG
			
<ul style="list-style-type: none"> • Monitoring for mains loss, load or SSR failure • Ratings up to 530 VAC, 110 A • DC control voltage, DC external supply • Normally open or normally closed alarm output • Approvals CE - UR - CSA - EAC - UKCA 	<ul style="list-style-type: none"> • Monitoring for system fault (mains loss, load loss, SSR open and short circuit), SSR internal error and supply out of range • Ratings up to 660 VAC, 90 AAC • DC control voltage, DC external supply • Transistor output for remote alarm signalling • Approvals CE - UR - CSA - cULus [RGC] - EAC - UKCA 	<ul style="list-style-type: none"> • Zero Cross switching with integrated current measurement • Partial load failure detection (1/6) • Monitoring for system malfunction with alarm output • Ratings up to 660 VAC, 90 AAC, 18000 A²s • Approvals: CE - UR - CSA - cULus [RGC] - EAC - UKCA 	<ul style="list-style-type: none"> • PROFINET, EtherNet/IP™ or Modbus RTU • 32 SSRs per bus chain • ON/OFF, Full cycle, Advanced full cycle, Burst, Phase angle and soft start switching • Read-outs: current, voltage, frequency, power, energy, running hours and diagnostics • Ratings up to 660 VAC, 90 AAC • Approvals: CE - cULus - UR - CSA - EAC - UKCA
Integrated over temperature protection RGC..P	Peak Switching RM1C	Heatsinks	Accessories
			
<ul style="list-style-type: none"> • Ratings up to 660 VAC, 85 AAC, 18000 A²s • Output protected against overheating, automatic re-start after cool down • Transistor alarm output for remote signalling • Control ON and Fault LED indication • Approvals: CE - cULus - VDE - EAC - UKCA 	<ul style="list-style-type: none"> • Ideal for switching of transformers and highly inductive loads • Ratings up to 660 VAC, 100 A • DC control voltage • Control ON LED • Approvals: CE - cURus - CSA - EAC - UKCA 	<ul style="list-style-type: none"> • A wide range of heatsinks suitable for DIN, panel or thru wall mounting • Thermal resistance values from 5.4 to 0.4°C/W • 24 VDC, 115 VAC or 230 VAC supply voltage for heatsinks with integrated fan • RoHS compliant 	<ul style="list-style-type: none"> • A wide range of other accessories suitable for use with SSRs: thermal pads, touch protection covers, varistors, terminal adaptors, cable accessories • Optionally pre-assembled from factory • All accessories are RoHS compliant

Soft starters

Carlo Gavazzi offers a comprehensive range of soft starting and motor reversing solutions for single and three phase squirrel cage a.c. induction motors. Carlo Gavazzi offers solutions specifically designed for scroll compressors (RSBS, RSBD, RSBT, HDMS). For other applications such as centrifugal pumps, ventilators, dryers, mixers, fans, hydraulic pumps and piston compressors, general purpose solutions such as the RSGD and RSGT are available. Carlo Gavazzi soft starters are designed with self-learning algorithms for ease of use and better load matching. The RGTS is a fully solid-state soft starter for single phase applications that require high frequency switching. In addition, customized solutions to satisfy specific customer requests can be provided.

Scroll compressor soft starters RSBD 45 mm



- Operational current: 12 to 45 A
- Self-learning algorithm with current balancing
- Top of ramp and alarm relay indication
- Max. starts per hour: 12
- Approvals: CE - cULus - EAC

Scroll compressor soft starters RSBD 75 mm



- Operational current: 55 to 95 A
- Self-learning algorithm for current reduction
- No user adjustments required
- Max starts per hour: 12
- Approvals: CE - cULus - EAC

Scroll compressor soft starters RSBT 45 mm



- Operational current: 16 to 32 A
- Self-learning algorithm with high pressure function
- No user adjustments required
- Optional: serial communication (Modbus) [Version: VC1HP]
- Max. starts per hour: 12
- Approvals: CE - cULus - VDE - CCC

Scroll compressor soft starters RSBT 120 mm



- Operational current: 55 to 95 A
- Self-learning algorithm for improved current reduction
- Optional: serial communication (Modbus) [Version: VC]
- Max. starts per hour: 12
- Approvals: CE - cULus - CCC - EAC

General purpose soft starters RSGT 45 mm



- Operational current: 12 to 25 A
- Operational voltage: 220 - 600 VAC
- Self-learning algorithm with current ramp and current limit
- 3-phase control with internal bypass
- Optional: serial communication (Modbus) [Versions: V10C]
- Approvals: CE - cULus - EAC

General purpose soft starters RSGT 75 mm/120 mm



- Operational current: 32 to 90 A
- Operational voltage: 220 - 600 VAC
- Self-learning algorithm with current ramp and current limit
- 3-phase control with internal bypass
- Serial communication (Modbus) on all models
- Approvals: CE - cULus - EAC

General purpose soft starters RSGD 45 mm



- Operational current: 12 to 45 A
- Operational voltage: 220 - 600 VAC
- Self-learning algorithm with current ramp and current limit and current balancing
- 2-phase control with internal bypass
- Optional: motor overload protection (Class 10) [Versions: V210]
- Approvals: CE - cULus - CCC - EAC

General purpose soft starters RSGD 75 mm



- Operational current: 55 to 100 A
- Operational voltage: 220 - 600 VAC
- Self-learning algorithm with current ramp and current limit and current balancing
- PTC input and remote reset of alarms
- Serial communication (Modbus) on all models
- Approvals: CE - cULus - CCC - EAC

Motor reversing relay RR2A



- Operational current: up to 11 A
- Motor reversing relay
- Built-in interlock function
- Integrated voltage transient protection
- Approvals: CE - UL - cUL

1-phase solid state soft starter RGTS



- Operational current: 12/16/25 A
- Operational voltage: 100 - 240 VAC
- 100 kA short circuit current rating
- Max. starts per hour: 10
- Approvals: CE - cULus

1-phase compressor soft starter RSBS



- Operational current: 32 A
- Current limit starting with a high pressure function
- Max. starts per hour: 10
- Approvals: CE - cULus - EAC

1-phase dynamic motor starter HDMS



- Operational current: 12 to 37 A
- Eliminates the need for a start capacitor typically used to start single phase motors
- >70% start current reduction on scroll compressors and submersible pumps
- Tool-free terminals
- Approvals: CE - cULus

Variable frequency drives

Carlo Gavazzi offers a range of variable frequency drives (VFDs) for general purpose applications (RVLF). Carlo Gavazzi also offers PC software that facilitates parameter configuration and also makes it is easy to download the configuration onto multiple VFDs.

General purpose VFD RVLF 1-phase 100 V



- V/F Control + Sensorless Vector control
- Input voltage 1-phase 100-120 VAC
- 0.4 kW and 0.75 kW
- Built-in RJ45 for MODBUS and BACNet communication
- Panel mount or DIN-rail (with accessory)

General purpose VFD RVLF 1-phase 200 V



- V/F Control + Sensorless Vector control
- Input voltage 1-phase 200-240 VAC
- 0.4 kW to 2.2 kW
- Built-in RJ45 for MODBUS and BACNet communication
- Built-in Class 2 EMI filter
- Panel mount or DIN-rail (with accessory)

General purpose VFD RVLF 3-phase 200 V



- V/F Control + Sensorless Vector control
- Input voltage 3-phase 200-240 VAC
- 0.4 kW to 2.2 kW
- Built-in RJ45 for MODBUS and BACNet communication
- Panel mount or DIN-rail (with accessory)

General purpose VFD RVLF 3-phase 480 V



- V/F Control + Sensorless Vector control
- Input voltage 3-phase 380-480 VAC
- 0.75 kW to 11 kW
- In built RJ45 for MODBUS and BACNet communication
- Built-in Class 2 EMI filter
- Panel mount or DIN-rail (with accessory)

DIN-clip RVLF size A



- Plastic DIN-clip and mounting screws for RVLF Size A models

DIN-clip RVLF size B



- Plastic DIN-clip and mounting screws for RVLF Size B models

USB connection cable



- Isolated USB to RJ45 cable for RVLF configuration

Industrial relays and Sockets

Carlo Gavazzi offers a comprehensive range of electromechanical relays for industrial automation. These are available in plug-in and PCB mounting. Many of the relays come as standard with a push-to-test button as well as a LED indicator. Carlo Gavazzi relays are frequently used in control panels, in HVAC control systems, pump and compressor control and electronic and consumer products. They are typically used to switch loads such as heaters, lights and motors. Carlo Gavazzi also offers a complete range of sockets (DIN-rail mounting) for industrial and PCB relays.

Industrial RCP	Midi industrial RPY	Midi industrial RMI	Power NF/NB
----------------	---------------------	---------------------	-------------



- 8 or 11-pin socket mounting
- 2 or 3 change-over contacts
- Matching sockets available
- AC coils 6 to 230 VAC/DC coils 6 to 110 VDC
- Standard with LED, Push arm and Flag



- High switching power
- 10 or 16 A switching capacity
- 1 or 2 or 3 or 4 pole configuration
- DC coils from 6 to 110 V/AC coils from 6 to 230 V
- Flanged pins 5 mm (0.20")



- High switching power
- Contact rating 10 A [RMI2] 5 A [RMI4]
- 2 pole [RMI2] 4 pole [RMI4] configuration
- AC coils 6 V to 230 V/DC coils 6 to 110 V
- Standard with LED, Push arm and Flag



- Switching capacity 30 A
- DC coils 6 to 110 VDC / AC coils 12 to 240 VAC
- 1 or 2 normally open contact
- Faston terminals [NF] / PCB terminals [NP] / Bolt terminals [NB]

Power CF/CS	Slim RSLM	Slim industrial RPYS	Slim Sockets ZPYS
-------------	-----------	----------------------	-------------------



- High switching power
- Switching capacity 30 A
- 2 normally open contacts, 2 change over contacts
- DC coils from 5 to 110 V / AC coils from 24 to 277 V
- Faston terminals / PCB terminals



- 5 mm width
- Switching capacity 6 A
- 1 normally open contacts or 1 change over contact
- DC coils from 12 to 60 V
- PCB terminals



- Slim Relay solution
- Basic and LED+Test button versions
- 8 or 12 A switching capacity
- 1- or 2- pole configuration
- DC coils 12 - 24 V, AC coils 24 - 115 - 230 V



- Sockets for RPYS relays
- Rated voltage 300 VAC
- Rated current 16 A
- Screw and Push-in terminals
- Pre-mounted solutions with Relay + Socket + Clamp

Sockets ZPD	Sockets ZMI	Sockets ZPY	Sockets ZRLS
-------------	-------------	-------------	--------------



- Sockets for RCP relays
- Rated voltage 300 VAC
- Rated current 10 A
- Terminal type screw cage
- Contact material nickel plated - CuZn33



- Sockets for RMI relays
- Rated voltage 300 VAC
- Rated current 10 A
- Terminal type screw cage
- Contact material Cu Ni



- Sockets for RPY relays
- Rated voltage 300 VAC
- Rated current 16 A
- Terminal type screw cage
- Contact material nickel plated - CuZn33



- Sockets for RSLM relays
- Rated voltage up to 250 VAC
- Rated current 6 A
- Screw terminals or spring terminals
- Options: various AC/DC voltage inputs

Switching power supplies

Carlo Gavazzi presents a complete range of power supplies and battery chargers for both the automation industry and building automation. These are available in 3 different package types: cabinet DIN-rail mounting, low profile DIN-rail mounting for electrical distribution panels and the enclosed type. Power supplies are also available with DC, 1-phase, 2-phase and 3-phase inputs. Output voltages span from 5 to 48 VDC, with output powers from 5 W to 960 W. Aside from the power supplies there are also other available devices such as battery chargers and redundant controller modules. The battery chargers are available in 2 powers, 30 W and 60 W, and 2 voltages, 12 V and 24 V. Redundancy modules can manage 2 inputs from power supplies in order to guarantee that the DC voltage is always provided even in the case of failure of one power supply.

SPD 1 - DIN-rail 1-phase power supplies	SPD 2 - DIN-rail 100 W 2-phase power supply	SPD 3 - DIN-rail 3-phase power supplies	SPMA - Low profile DIN-rail power supplies
--	--	--	---



- From 5 to 480 W output power, 110 V or 240 VAC 1-phase or 120 V to 370 VDC input
- Power OK output
- Screw or spring terminals
- Adjustable output
- TUV approved, cULus Listed, Class 2 UL1310 (up to 92 W), Class I Div 2



- 100 W output power, 340 to 575 VAC (2-phases) or 480 - 820 VDC input
- Power OK output
- Passive PFC
- High efficiency, compact dimensions
- Class 1, Div 2 certified; TUV approved, cULus listed




- From 120 to 960 W output power, 340 - 575 VAC (2- or 3-phases) or 480 - 820 VDC input
- Power OK output
- Active PFC
- Parallel operation switch
- TUV approved, cULus listed



- From 12 to 100 W output power, 85 or 264 VAC or 120 to 350 VDC input
- Overvoltage, Overload and Short circuit protection
- Internal input filter
- 4 kV insulation, UL Class 2 output
- CE - cULus - cURus
UL 1310 Class 2 (up to 91.92 W)
UL 121201 Class I Div 2

SPPC Enclosed type 25 W ~ 800 W	SPDM - DIN-rail 1-phase power supplies	SPDC - DIN-rail 1-phase power supplies	SPM5BC - 30 W and 60 W battery chargers
--	---	---	--



- 110 V / 240 VAC or 120 to 370 VDC input
- Wide operating temperature -25°C to 70°C
- Conformal coated PCB
- Available with PFC
- Cooling fan w/ speed control
- Adjustable output
- cURus recognized



- 30 W to 240 W output power, 110 VAC / 240 VAC or 120 V to 370 VDC input voltage
- Compact dimensions
- Adjustable output
- DC Ok indication
- TUV approved, cULus listed, Class 2 UL1310 (up to 75 W)



- 120 W and 480 W output power, 110 VAC / 240 VAC or 120 V to 370 VDC input voltage
- Very compact
- Parallel connection output
- DC Ok Output
- TUV approved, cULus listed



- Universal AC input 90 VAC to 264 VAC
- For lead-acid batteries
- 12 V or 24 V output
- Battery polarity protection

SPUC - 30 A 12/24 VDC UPS Controller	SPUBC - 120 W 24 VDC UPS & power supply	SPD24RM20 redundant module 20 A	SPUBAT24 DIN-rail battery bank 1.2 to 12 Ah
---	--	--	--



- DC input 12 or 24 V / Uninterrupted DC output 12 or 24 V
- Up to 30 A output
- For batteries up to 25 Ah
- DIN-rail mounting
- TUV approved, cULus listed



- 24 V power supply, Battery Charger and UPS
- Smart battery diagnostics and Charge management
- For batteries up to 50 Ah
- DIN-rail mounting
- cURus recognized



- 24 V redundant power supply management
- 2 DIN-rail modules size / 2 "Power ready" signal outputs
- Up to 20 A output
- Simple installation and setup
- TUV approved, cULus listed



- Stainless steel battery rack for UPS and battery chargers
- 24 V VRLA Battery bank
- Front panel screw terminals for easy connection
- DIN-rail or wall mounting
- Built-in easily replaceable fuse

Digital panel meters

Carlo Gavazzi offers a comprehensive range of digital panel meters, digital displays (for current meters, ammeters, voltmeters, frequency meters, temperature meters and temperature controllers, tachometers, and rate meters) and signal conditioners for OEM, panel builder, instrumentation and MRO customers.

Covering most input types, our digital panel meters are well suited to any display requirements. With the modular types it is possible to realize any sort of configuration and the analogue signal can also be retransmitted to show the readings. The displayed colour can be set to change at specific thresholds, allowing any type of anomaly to be easily seen.

Touch display	Modular indicator/ controller UDM35	Modular indicator/ controller UDM40	Modular controller USC
---------------	--	--	---------------------------



- 7" colour display
- Easy setup of graphic pages and functions with the powerful Wizard software
- BACnet, Modbus and KNX gateway
- Support viewing of IP cameras
- Ethernet connection and RS485 serial port



- 3½ DGT LED
- AC/DC V-I, Temperature and Resistance, Speed, Frequency and Period measurement
- Up to 4 independent alarm set-points, 20 mA/10 VDC analogue output
- RS485 or RS232, MODBUS RTU
- Panel mounting
- Degree of protection: IP67, NEMA12, NEMA4x



- 4 DGT LED
- AC/DC V-I, Temperature and Resistance, Speed, Frequency and Period measurement
- Up to 4 independent alarm set-points, 20 mA/10 VDC analogue output
- RS485 or RS232, MODBUS RTU
- Panel mounting
- Degree of protection: IP67, NEMA12, NEMA4x



- Modular signal's conditioner
- AC/DC V-I, Temperature and Resistance, Speed, Frequency and Period measurement
- Up to 4 independent alarm set-points, 20 mA/10 VDC analogue output
- RS485 or RS232, MODBUS RTU
- DIN-rail mounting
- Degree of protection: IP20

Indicator LDI3	Indicator LDM30	Indicator/controller LDM35H	Indicator/controller LDM40
-------------------	--------------------	--------------------------------	-------------------------------



- 3 DGT µP-based
- AC V-I
- 20 Selectable CT/VT primary ranges
- 48 x 96 mm
- Panel mounting
- Degree of protection: IP50 (IP65 on request)



- 3 DGT LED + "0" dummy µ-based
- AC V-I
- Dip-switch-selectable ranges
- 48 x 96 mm
- Panel mounting
- Degree of protection: IP50 (IP65 on request)



- 3½ DGT LED
- AC/DC V-I
- Up to 2 independent alarm set-points
- 48 x 96 mm
- Panel mounting
- Degree of protection: IP65



- 4 DGT LED
- AC/DC V-I
- Up to 2 independent alarm set-points, 20 mA/10 VDC analogue output, RS485 MODBUS RTU
- 48 x 96 mm
- Panel mounting
- Degree of protection: IP65

Indicator DI3-DIN	Indicator DI3-72
----------------------	---------------------



- 3 DGT µP-based
- AC/DC V-I, Frequency
- 20 Selectable CT/VT primary range
- 3-DIN modules
- DIN-rail mounting
- Degree of protection: IP40



- 3 DGT µP-based
- AC/DC V-I, Frequency
- 18 Selectable CT/VT primary range
- 72 x 72 mm
- Panel mounting
- Degree of protection: IP50 (IP65 on request)

Power analyzers and current transformers

Main electrical metering is essential to monitor all the electrical variables coming from the submetering. Installations are becoming more and more demanding, some of them powering critical loads, so power quality with harmonic analysis is vital. Carlo Gavazzi's range provides various mounting and installation solutions to meet different application requirements. In many cases the meters, in an electrical installation, have to measure high currents, which is why Carlo Gavazzi offers a comprehensive range of current transformers, compatible with both the main meters and the submeters.

Energy transducer ET112



- DIN-rail mounting
- 1-phase, 120 or 240 VAC, 100 AAC
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port, optical port
- Approvals: CE

Energy transducer ET330



- DIN-rail mounting
- 400 to 480 V_{LL} AC, 5 AAC
- Class 0.5S (kWh), 0.2% RDG (V, A)
- RS485 Modbus port, optical port
- Approvals: CE - cULus

Energy transducer ET340



- DIN-rail mounting
- 208 to 400 V_{LL} AC, 65 AAC
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port, optical port
- Approvals: CE

Power analyzer WM15



- Panel mounting
- 208 to 600 V_{LL} AC, 5(6) A
- Class 1 or Class 0.5S (kWh), 0.5% RDG (V, A)
- Pulse/alarm output, optional Modbus RS485 port
- Approvals: CE - MID - cULus

Modular power analyzer WM20



- Panel mounting
- 208 or 690 VAC, 5 AAC
- Class 0.5S (kWh), 0.2% RDG (V, A)
- Up to 2 outputs, optical port, Modbus RS485 and Ethernet, BACnet MSTP and IP, Profibus
- Approvals: CE - cULus

Modular power quality analyzer WM30



- Panel mounting
- 208 or 690 VAC, 5 AAC
- Class 0.5S (kWh), 0.2% RDG (V, A)
- Up to 4 outputs, optical port, Modbus RS485 and Ethernet, BACnet MSTP and IP, Profibus
- Approvals: CE - cULus

Modular power quality analyzer WM40



- Panel mounting
- 208 or 690 VAC, 5 AAC
- Class 0.5S (kWh), 0.2% RDG (V, A)
- Up to 6 inputs, up to 8 outputs, optical port, Modbus RS485 and Ethernet, BACnet MSTP and IP, Profibus
- Approvals: CE - cULus

Modular branch circuit analyzer WM50



- Panel mounting
- 208 or 690 VAC, 5 AAC + TCD
- Main unit: Class 0.5S (kWh), 0.2% RDG (V, A). TCD: 0.5% (V, A)
- Up to 96 sub-metering 65 A ch. Up to 6 digital inputs, up to 6 outputs, optical port, Modbus RS485 and Ethernet
- Approvals: CE - cULus

Power transducer CPA




- Contactless power analyzers
- 1-phase AC (from 1 to 400 Hz) or DC systems
- RS485 communication port (Modbus)
- Current range:
[CPA050] 50 AAC / 50 ADC
[CPA300] 300 AAC / 400 ADC
- Voltage range: 800 VAC / 1000 VDC
- Approvals: CE - cURus

Power transducer CPT



- DIN-rail mounting
- 208 or 690 VAC, 1 or 5 AAC
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 port, relay, open collector, or analogue output
- Approvals: CE - cURus - CSA

Current transformer CTD X



- DIN-rail, cable or bus-bar mounting
- Solid core current transformers
- Primary: from 40 to 1600 AAC
- Secondary: 5 A or 1 A
- Approvals: EN 61869-2 - cURus - CSA

Current transformer CTD V/H/S



- Bus-bar mounting
- Solid or split core current transformers
- Primary: from 100 to 4000 AAC
- Secondary: 5 A or 1 A
- Approvals: EN 61869-2 - cURus - CSA

Energy analyzers and quick-fit solutions

A comprehensive range of energy meters and analyzers focused on submetering and cost allocation. Carlo Gavazzi provides a solution to industrial, commercial, residential and power generation applications where accuracy, standard compliance (including MID), electrical variable metering, analysis and communication are all important factors. Up-to-date designs, quality, attention to details, such as installation features and installation time, all mean that Carlo Gavazzi products are very competitive in the market. A full retrofit range of meters offering metering and monitoring solutions to meet every need can be found in our product portfolio.

Energy analyzer EM110 - EM111 - EM112	Energy analyzer EM530 - EM540	Energy analyzer EM24	Quick-fit energy meter EM270 and TCD X
--	----------------------------------	-------------------------	---



- DIN-rail mounting
- 1-phase, 120 or 240 VAC, 45 or 100 A direct connection, 5 A or 333 mV CT input
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port, M-bus port, or open collector output
- Approvals: CE - MID - cULus



- DIN-rail mounting
- 208 to 415 VLL AC, CT input [EM530] or 65 A direct connection [EM540]
- EM540: class 1 (kWh)
- EM530: class 0.5S (kWh)
- RS485 Modbus port, M-bus port, or open collector output
- Approvals: CE - cULus - MID



- DIN-rail mounting
- 208 to 400 VLL AC, CT or 65 A direct connection
- Class 1 (kWh), 0.5% RDG (V, A)
- 3 digital inputs. Wired or wireless M-bus, RS485 Modbus or Modbus TCP
- Ethernet port
- 2 digital outputs
- Approvals: CE - cULus - MID



- DIN-rail and panel mounting
- 230 or 400 VAC, 160 to 630 AAC measured by up to 2 TCD X triple current transformers
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port, static output
- Approvals: CE - cULus

Quick-fit energy meter EM271 and TCD M	Quick-fit energy transducer ET272 and TCD M	Quick-fit energy meter EM280 and TCD06B	Retro-fit energy analyzer EM210AV - MV
---	--	--	---



- DIN-rail and panel mounting
- 230 or 400 VAC, 60 to 400 AAC measured by up to 2 TCD M split-core triple current sensors
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port, static output
- Approvals: CE - cULus



- DIN-rail mounting
- 230 or 400 VAC, 60 to 400 AAC measured by up to 2 TCD M split-core triple current sensors
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port with self-addressing capability
- Approvals: CE - cULus



- DIN-rail and panel mounting
- 230 or 400 VAC, 32 AAC measured by 6-channel TCD06B current transformer block (solid or split core)
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port, static output
- Approvals: CE - cULus



- DIN-rail and panel mounting
- 230 or 400 VAC, CT input [AV] or 60 to 800 AAC measured by CTV or ROG current sensors [MV]
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port, static output
- Approvals: CE - cULus

Rogowski current sensors ROG4X	Current sensor CTV	Split-core current transformers CTA	DC Energy meter VMU E - VMU X
-----------------------------------	-----------------------	--	----------------------------------



- Cable mounting
- Rogowski split core current sensors for EM210 MV
- Primary: up to 4000 AAC
- Secondary: direct connection to EM210 MV without any external converter
- Approvals: CE - cURus



- Cable mounting
- Miniature split core current sensors
- Primary: from 60 to 800 AAC
- Secondary: 333 mV
- Approvals: CE - cURus



- Cable mounting split-core
- current transformers
- Primary: from 100 to 600 AAC
- Secondary: 5 A
- Approvals: CE - cURus



- DIN-rail mounting
- 400 VDC, 1000 A (20 A direct)
- Class 1 (kWh), 0.5% RDG (V, A)
- RS485 Modbus port or static output
- Approvals: CE

Remote data reading and Data aggregation solutions

The mounting of a power analyzer or an energy meter on a power distribution unit is not enough to effectively manage the whole electrical installation, because the data available on the display would seldom be read and controlled. To be effective, remote reading and reporting of historical data is required. A control room can gather the readings while the data can be analysed and used as a basis for decision-making, all thanks to a fully automated system. Carlo Gavazzi can provide solutions for small, medium size and large plants for energy efficiency monitoring, photovoltaic monitoring and datacenter monitoring.

UWP 3.0	VMU-C EM	VMU-M/VMU-P/VMU-O EM	VMU-MC/VMU-OC
---------	----------	----------------------	---------------



- Web-Server, gateway and controller for energy efficiency management applications.
- Micro PC with monitoring and control features over multiple buses
- Datalogging, remote communication and data analysis capabilities
- Dashboards and reports
- Advanced management of input and output signals for monitoring and control functions



- Embedded solution for remote data reading and energy management in Datacenter applications
- Micro PC with Web-Server and Web service capability
- Data and event logging capability
- Integrated data management functions
- Monitoring of Energy variables and basic I/O module functions



- VMU-M master unit with local datalogging to manage up to 15 VMU 1-DIN units
- VMU-P unit for environmental monitoring
- VMU-O unit with digital inputs/outputs reading



- Pulse counter concentrator
- Modular solution to collect from 2 to 11 pulse counter SO inputs
- Totalizers calculation and Modbus/RTU communication
- VMU-MC: master module with 2 SO inputs
- VMU-OC: additional module with 3 SO inputs
- Plug'n'play connection to UWP 3.0 or VMU-C EM

Em ² -Server	VMU-C PV	Eos-Array / Eos-Array Lite	Environmental sensors PVS-1
-------------------------	----------	----------------------------	-----------------------------



- Cloud or On-Premise solution for multi-site energy management
- Virtual machine software integrating database and web-server
- Data aggregation from up to 100 sites/installations
- Advanced data management functions
- Management of up to 100 UWP 3.0 or VMU-C EM units



- Embedded solution for remote data reading in solar applications
- Micro PC with Web-Server and Web service capability
- Data and event logging capability
- Integrated data management functions
- Management of up to 64 inverters/energy meters and 15 Eos-Array groups



- VMU-M master unit with local datalogging to manage up to 15 VMU 1-DIN units
- VMU-S string unit for basic or advanced string control, and string efficiency monitoring
- VMU-P unit for environmental monitoring
- VMU-O unit with digital inputs/outputs reading



- Solar irradiance sensor for photovoltaic applications
- Crystalline silicon cell
- Compact and rugged IP67 aluminium case
- UV resistant resin encapsulation
- Available with 0-100 mV or 4-20 mA output

Modbus to M-bus converter VMU B	M-Bus to Modbus/TCP Gateway SIU-MBM	Communication interface OPTOPROG	UWP A / UWP M long range wireless solution
---------------------------------	-------------------------------------	----------------------------------	--



- DIN-rail mounting
- RS485 Modbus master
- For EM23, EM210, EM270, EM271, EM280, WM15
- M-bus output port
- Approvals: CE



- M-Bus to Modbus/TCP gateway
- Up to 20 M-Bus devices (SIU-MBM-01, SIU-MBM-02)
- Up to 160 M-Bus devices (SIU-MBM-01-160)
- Up to 32 wireless M-Bus devices (SIU-MBM-02)
- Set-up by free UCS software
- Approvals: CE















- Bluetooth and USB interface for meters and analysers with optical port
- Compatible with WM20, WM30, WM40, WMS0 and ET100, ET300 families
- Compatible with UCS PC software and UCS Mobile Android APP
- Battery powered
- Approvals: CE - FCC - IC - Bluetooth



- Comprehensive solution for integrating CG meters and power analysers into public or private wireless monitoring networks
- Long range wireless (EU868 and US915 Bands, Europe and North America)
- Compatible with CG meters and UWP 3.0
- Universal power supply
- Approvals: CE - LoRaWAN® (UWP A)

Building automation

Carlo Gavazzi's modular concept for home and building automation is based on a patented digital bus, the two-wire Dupline® controlling and monitoring applications for example lighting, roller blinds, heating, air-conditioning and alarms. This innovative system allows considerable savings in energy consumption, increasing comfort and safety. Operations, services and maintenance are simplified, with complete status overview anytime and anywhere. It can also be interfaced to any building automation system via BACnet/IP.

Master units	Dupline® bus generators	Wireless bus generator and repeater	DALI bus generator and Ballast
			
<ul style="list-style-type: none"> • Web-Server, gateway and controller for energy efficiency management and building automation. It provides easy integration with local or remote BMS/EMS/Server solutions • Two RS485 ports (Modbus) • Protocols: BACnet, Modbus TCP/IP and RTU, HTTP/S, FTP/S, Data Push, SMTP, NTP, MQTT, Rest API • Dimensions: 2-DIN modules 	<ul style="list-style-type: none"> • Connection to UWP 3.0 via internal bus or terminals via the high speed bus • Up to 7 SH2MCG24 can be connected on the same network, taking into consideration the sum of SH2MCG24 and SH2WBU230N • Dimensions: 2-DIN modules 	<ul style="list-style-type: none"> • Connection to UWP 3.0 via internal bus or terminals via the high speed bus • Wireless transmission based on IEEE 802.15.4, @ 2.4 GHz • Max slaves per network: 250 • Max repeater hops: 4 • Operating distance: 700 m in the open air with a repeater • Dimensions: 2-DIN modules 	<ul style="list-style-type: none"> • DALI Master for Smart Dupline® • DALI driver for DT6 and DT8 LEDs • Up to 7 DALI masters on one Dupline® network • Up to 64 lighting actuators on one DALI bus • Tunable white management • Dimensions: 2-DIN modules
Repeater modules	Dimmer modules	Relay modules	Digital input modules
			
<ul style="list-style-type: none"> • Regenerates the Dupline® carrier signal with 300 mA output • Extends network length • Isolates the primary and secondary Dupline® • 230 VAC power supply • Dimensions: 2-DIN housing 	<ul style="list-style-type: none"> • Universal dimmer switch for R, L, C up to 500 W and LED loads • Automatic load detection for L, R, C loads • Integrated heat sink for temperature dissipation • Connection to other cabinet modules via local bus • Dimensions: 2-DIN modules 	<ul style="list-style-type: none"> • 4 separate output relays • LED-indications for supply, bus and output status • Push button for local on/off switching • Connection to other cabinet modules via local bus • Dimensions: 2-DIN modules 	<ul style="list-style-type: none"> • 4 digital inputs NPN, PNP, voltage free • The 4 inputs can be configured as contact or counter • LED indication for power supply, Dupline® bus, input activated • Connection to other cabinet modules via local bus • Dimensions: 2-DIN modules
Rollerblind modules	Light switches	PIR detectors + Luxmeter	Temperature displays
			
<ul style="list-style-type: none"> • Up/down control of 2 AC/DC rollerblind motors • LED indication for power supply, Dupline® bus, motor up, motor down • Push button for local on/off switching • Connection to other cabinet modules via local bus • Dimensions: 2-DIN modules 	<ul style="list-style-type: none"> • 4 individually programmable push buttons • 4 individually programmable LEDs for true response • Bus powered, no external supply required • B4X-LS4-U: Developed to fit into wall sockets and frames from Fuga, NIKO and Bticino • B5X-LS4-U: Developed to fit into wall sockets and frames from Elko, Gira and Jung 	<ul style="list-style-type: none"> • Passive infrared detector (PIR) • Detects movement and presence • Bus powered, no external supply required • Walk test: LED indication • Programmable sensitivity 	<ul style="list-style-type: none"> • Temperature controller with display • Shows current room, outdoor and auxiliary temperature • Bus powered, no external supply required • SHA: Developed to fit into wall sockets from Fuga, NIKO and Bticino • SHE: Developed to fit into wall sockets from Elko, Gira and Jung

Building automation

The Dupline® bus provides several advantages to building automation systems. The simplified wiring and high flexibility of the bus-powered sensors and decentralized I/O modules can provide considerable installation cost reductions. Due to the cost-effective design of the smart-house modules, this can be achieved by using materials with a cost comparable to the traditional hardwired solutions. The issue is to interface Dupline® and Energy Meters to the building automation controllers and building management systems and with the UWP 3.0 BACnet controller, all data points from Dupline® and Energy Meters are now automatically made available as BACnet objects, ready to be used by any building automation controller or BMS from the major suppliers.

Wireless light switches	Wireless relays	Wireless energy meter	Wireless dimmer
-------------------------	-----------------	-----------------------	-----------------



- 4 individually programmable push buttons
- Blue and red LEDs for wireless field power and battery level
- Battery supplied
- SHA4XWLS4: developed to fit into wall sockets and frames from Fuga, NIKO and Bticino
- SHE5XWLS4xFx: developed to fit into wall sockets and frames from Elko, Gira and Jung



- Small sized single relay output for eurobox mounting
- Energy reading
- Range up to 700 m in open air
- Load: 10 A/250 VAC
- Capacitive touch buttons for a plug&play replacement of standard switches (Bticino only)



- Small sized for eurobox mounting
- Values readout: A, V, W, Wdmd, VA, var, PF, kWh
- Range up to 700 m in open air
- Direct connection up to 16 A



- Universal dimmer switch for R, L, C up to 200 W and LED loads
- Automatic load detection for L, R, C loads
- Range up to 700 m in open air
- Capacitive touch buttons for a plug&play replacement of standard switches (Bticino only)

Decentral analogue input/output modules	Input module / Pulse counter	Wireless input module	Decentral relay modules
---	------------------------------	-----------------------	-------------------------



- Output modules with two 0-10 V outputs
- Input modules for thermistor, resistor and voltage measuring: pt1000, ni1000, 10K3 thermistor input, 1-11K resistor input, 0-10 V input, 4-20 mA
- Small dimensions for decentralized installations



- Input module with 4 configurable inputs: SO class B pulse counter or voltage free input
- Count values are stored in non-volatile memory
- Counts up to 99999999 with rollover
- Bus powered



- Input module with 4 configurable inputs: SO class B pulse counter or voltage free input
- Count values are stored in non-volatile memory
- Counts up to 99999999 with rollover
- Range up to 700 m in open air



- Small sized single relay output
- Load: 16 A / 250 VAC
- Withstands 130 A inrush current
- Bus powered

Environmental sensors	Weather station	HMI colour touch displays	Fire damper
-----------------------	-----------------	---------------------------	-------------



- CO₂, temperature and humidity sensors
- CO₂ measuring range: 0 to 2000 ppm
- Temperature measuring range: -20°C to 50 °C
- Humidity measuring range: 0 to 100 %R
- LCD Display and touch function to activate backlight and change signal type



- Light, wind, temperature measurement
- Ranges: 0 to 100K lux, 0 to 35 m/s, -40°C to 80°C
- Rain sensor included
- Integrated GPS receiver
- Modbus RS485 protocol















- 7", 10" and 15.6" colour HMI displays
- Fully programmable by the dedicated IDE software
- IIoT data distribution via MQTT and OPC UA
- BACnet, Modbus and KNX protocols with gateway/routing capabilities
- Ethernet, serial and USB ports



- I/O module to control two fire dampers
- Box ready for wall mounting near dampers
- Four contact inputs, two relay outputs 230 VAC / 5 A
- Power supply: 24 to 230 VAC
- Degree of protection: IP55

Parking guidance system

The Carpark 3 is a complete solution for guiding drivers directly to vacant parking bays. Displays with arrows and digits indicate which direction to drive and how many bays are available. Upon arrival, the vacant parking bays are easily spotted by looking for the bright LED lights. Each bay has an ultrasonic sensor that detects and indicates occupancy resulting in a high precision system. The outdoor solution with wireless sensors and camera-based recognition detects cars in off-street or on-street parking areas. Furthermore, the system features smart building functions and products for lighting and ventilation control.

<p>45° Ultrasonic sensor</p>	<p>Vertical Ultrasonic sensor</p>	<p>Vertical Ultrasonic counting sensor</p>	<p>360° LED indicator</p>
			
<ul style="list-style-type: none"> • Ultrasonic sensor with a 45° detection angle for mounting at the entry to the parking space • Built-in bright RGB LEDs with 360° indication of space status (multi-colour) • Base holders for cable tray, ceiling and pipe/tube/conduit mounting • Dupline® 3-wire bus-powered • Dimensions: Ø116 x 76 mm 	<ul style="list-style-type: none"> • Vertical sensor to be mounted directly above the car • Built-in bright RGB LEDs with 360° indication of space status (multi-colour) • Base holders for cable tray, ceiling and pipe/tube/conduit mounting • Dupline® 3-wire bus-powered • Dimensions: Ø116 x 76 mm 	<ul style="list-style-type: none"> • Vertical sensor to be mounted in the driving lane for counting • Built-in bright RGB LEDs with 360° indication of space status (multi-colour) • Base holders for cable tray, ceiling and pipe/tube/conduit mounting • Dupline® 3-wire bus-powered • Dimensions: Ø116 x 76 mm 	<ul style="list-style-type: none"> • LED indicator to be mounted outside the parking space • Built-in bright RGB LEDs with 360° indication of space status (multi-colour) • Base holders for cable tray, ceiling and pipe/tube/conduit mounting • Dupline® 3-wire bus-powered • Dimensions: Ø116 x 50 mm
<p>Carpark Master generator</p>	<p>Carpark Controller</p>	<p>Carpark Server</p>	<p>Carpark Display interface</p>
			
<ul style="list-style-type: none"> • Generator of power and Dupline® bus communication on 3 wires • Connected as a slave to the Carpark controller UWP 3.0 • Connects up to 90 Carpark sensors via Dupline® 3-wire bus • Dimensions: 2-DIN housing • Powered by 28 VDC 	<ul style="list-style-type: none"> • Parking guidance, booking, carpark management, smart building, data logger and energy monitoring in one controller • Protocols: BACnet, Modbus TCP/IP and RTU, HTTP/S, FTP/S, Data Push, SMTP, NTP, MQTT, Rest API • Built-in webserver with user interface for carpark management software 	<ul style="list-style-type: none"> • Carpark server with capability of linking up to 10 UWP 3.0 together in larger systems • Built-in webserver with user interface for carpark management software • Data export in excel format • Powered by 24 VDC • Dimensions: 2-DIN housing 	<ul style="list-style-type: none"> • Interface between the Dupline® bus and display • RS485 serial connection to the display • LEDs for indication of communication status • Powered by 24 VDC • Dimensions: 2-DIN housing
<p>Carpark Baseholders</p>	<p>Carpark Displays with symbols and digits</p>	<p>Carpark Displays with symbols and digits</p>	<p>Carpark Displays with running text</p>
			
<ul style="list-style-type: none"> • Base holders for Carpark sensors and LED indicators • To be mounted either on rail, ceiling or pipe/tube/conduit • Dimensions: Ø116 x 24 mm (type A) / Ø116 x 44 mm (Type B) • Wire terminals built into base holder for easy change of sensor • On-board address chip with SIN code 	<ul style="list-style-type: none"> • Display with configurable symbols and digits • Bright RGB LED • Dimensions: 255 x 128 x 80 mm • Display resolution: 16 x 32 pixel • Indoor and outdoor installation • Visible at a distance of more than 50 m • RS485 and API communication • 24 VDC powered 	<ul style="list-style-type: none"> • Display with configurable symbols and digits • Bright RGB LED • Dimensions: 510 x 128 x 80 mm • Display resolution: 16 x 64 pixel • Indoor and outdoor installation • Visible at a distance of more than 50 m • RS485 and API communication • 24 VDC powered 	<ul style="list-style-type: none"> • Display with configurable symbols and digits and running text • Bright RGB LED • Dimensions: 510 x 255 x 80 mm • Display resolution: 32 x 64 pixel • Indoor and outdoor installation • Visible at a distance of more than 50 m • RS485 and API communication • 24 VDC powered

Fieldbuses - Industrial and DuplineSafe

Dupline® is a field and installation bus that offers unique solutions for a wide range of industrial applications. The system is capable of transmitting multiple digital and analogue signals over several kms, via an ordinary 2-wire cable. Its modular design and simple operating principle enables it to be implemented easily in new or existing applications. Solutions can be engineered by combining products from the wide range of Dupline® modules, including digital and analogue I/O modules, PLC and PC interfaces, HMIs and Modems. All modules in an installation connect to the same 2-wire cable, which is used to exchange data between modules and between a central controller and modules.

Channel generator	Fieldbus gateways	Digital input modules - DIN	Analogue input modules - decentral
-------------------	-------------------	-----------------------------	------------------------------------



- Generates Dupline® carrier signal
- Up to 128 Dupline® channels
- 2 and 3-wire operation with DC-power on the 3rd wire
- All Dupline® protocols are supported
- 24 VDC power supply
- Dimensions: 2-DIN housing

- Gateways for Profibus-DP, Devicenet, Modbus-RTU, Modbus/TCP
- Built-in channel generator
- Split I/O option
- AC and DC power supply
- DIN-rail mounting

- Contact and voltage input modules
- Relay and solid state output modules
- Bus-powered types
- AC and DC power supply
- DIN and decentral mounting

- 4 universal analogue inputs or outputs
- Types: 0-20 mA, 4-20 mA or 0-10 V
- Galvanically isolated inputs
- AC and DC power supply
- Dimensions: 4-DIN housing

Repeaters	Programming and test units	DuplineSafe output module	DuplineSafe input module
-----------	----------------------------	---------------------------	--------------------------



- Repeater for extending the Dupline® transmission distance
- Optical repeaters allow part of the Dupline® system to run on multimode fibre
- Dimensions: 4/8-DIN housing

- Programming tool for assigning addresses to Dupline® modules
- Test unit for monitoring and control of Dupline® channels
- Handheld
- Battery / bus powered

- Configurable safety relay
- Monitors up to 63 safety switches connected via Dupline®
- Force guided contacts
- TUV approved for SIL3
- Dimensions: 8-DIN housing

- Input module for E-stops and safety pull cords
- Transmits dynamically on two Dupline® channels
- TUV approved for SIL3
- Powered from the bus
- Dimensions: 57 x 36 x 16 mm

DuplineSafe gateways	DuplineSafe repeater	DuplineSafe optical converter	DuplineSafe programmer
----------------------	----------------------	-------------------------------	------------------------



- Profinet, Profibus-DP and Modbus-RTU gateways for DuplineSafe monitoring
- Can also monitor and control standard Dupline® signals in the same system
- Dimensions: 8-DIN housing

- Repeater for extending the DuplineSafe transmission distance
- Isolation between primary and secondary Dupline®
- Can be cascaded
- Dimensions: 8-DIN housing

- Optical repeaters allow part of the DuplineSafe system to run on multimode fibre
- Electrical-to-optical and optical-to-electrical units
- Dimensions: 4-DIN housing

- Optical repeaters allow part of the DuplineSafe system to run on multimode fibre
- Electrical-to-optical and optical-to-electrical units
- Dimensions: 4-DIN housing

Monitoring relays

Carlo Gavazzi offers a comprehensive range of monitoring relays for the detection of: phase loss, incorrect phase sequence, phase unbalance, over/under current, over/under load, over/under frequency, over/under voltage and overtemperature. Our products include monitors for: current, voltage, power, power factor, 3-phase systems, motor temperature and also current transformers. These monitors can be used in a wide range of applications for protecting motors against improper supply and overload (elevators, compressors, pumps, air conditioning systems, mixing tanks), and also protect properties against the risk of fire caused by loss of insulation or current leaks.

3-phase relays DPA51/DPA52



- Phase sequence
- Phase loss/regenerated voltage detection
- No setup required
- 5 A SPDT relay output

3-phase relays DPA55



- Phase sequence
- Phase loss
- Voltage window
- Incorrect connection proof (208-480 VAC power supply)
- 5 A SPDT relay output

3-phase relays DPB51/DPB52



- Phase sequence
- Phase loss
- 3P systems, 3P+N systems [DPB51]
- Independent overvoltage and undervoltage settings
- Adjustable alarm ON delay
- 5 A SPDT relay output

3-phase relays DPB01



- 3P systems, 3P+N systems, up to 400 Hz [CM44]
- Phase sequence and phase loss
- Independent overvoltage and undervoltage settings
- Adjustable alarm ON delay
- 8 A SPDT relay output

3-phase+N relays DPB02



- 3P systems, 3P+N systems, up to 400 Hz [CM44]
- Phase sequence and phase loss
- Voltage asymmetry setting
- Adjustable alarm ON delay
- 8 A SPDT relay output

3-phase+N relays DPC01



- 3P systems, 3P+N systems, up to 400 Hz [DM44]
- Phase sequence and phase loss
- Independent overvoltage and undervoltage setting + asymmetry and tolerance setting
- Separate adjustable alarm ON delays
- 2 x 8 A SPDT relay output

3-phase+N relays DPC02



- 3P systems, 3P+N systems, up to 400 Hz [DM44]
- Phase sequence and phase loss
- Independent overvoltage and undervoltage setting + overfrequency and underfrequency setting
- Separate adjustable alarm ON delays
- 2 x 8 A SPDT relay output

3-phase+N relays DPD02



- 3P systems, 3P+N systems, up to 400 Hz
- NFC device configuration and real time reading, through dedicated Android, iOS or Windows App
- All 3-phase voltage values can be monitored and combined to each relay
- Delays and hysteresis individually set for each variable
- 2 x 8 A SPDT relay output

Current relays DIA01/DIA02



- 0.5 - 5 AAC/DC [DIA01]
- 2 mA - 5 AAC/DC [DIA02]
- Overcurrent setting
- 8 A SPDT relay output

Current relays DIA53/EIS H



- 200 mA - 60 AAC range [EIS H]
- 2 A - 100 AAC range [DIA53]
- No power supply required
- Overcurrent setting [DIA53] ON/OFF monitoring (no adjustment required) [EIS H]
- NPN/PNP transistor output [DIA53] AC/DC solid state output [EIS H]

Current relays DIB01/DIB02



- 0.1 mA to 5 AAC/DC [DIB01]
- 60 mV/150 mV [DIB02]
- 2 A to 100 AAC [100A]
- Overcurrent or undervoltage setting
- Adjustable alarm ON delay
- 8 A SPDT relay output

Current transformers A82



- Wall mounting
- Cable hole
- 1-phase AC
- Input current up to 500 AAC
- Output 4 - 20 mADC, 0 - 20 mADC, 0 - 10 VDC

Monitoring relays

The possibilities for monitoring relays are countless: verification of machinery operation, detection of broken heater elements, lighting monitoring in critical areas (airport runways, buildings aircraft warning lights, tunnels), monitoring of ventilation fans and in building automation systems. Protection can be provided against people, fire, earth current leakage, or protecting from incorrect mains or cables connections. Also cabling and mounting is eased using different types of housing, double cage terminals, or pass-through connections for current measurement. Setup is always easy and accurate with the front dials and DIP switches.

Current transformers E83



- DIN-rail mounting
- Cable hole
- 1-phase AC
- Input current up to 50 AAC
- Output 4 - 20 mADC

Voltage relays DUA01/DUB01



- AC/DC TRMS over or undervoltage monitoring
- Range up to 500 VAC or DC
- Adjustable delay and hysteresis [DUB01]
- Programmable latching / inhibit
- 1 x 8 A SPDT relay output

Voltage relays DUA52



- DC battery undervoltage monitoring
- 12 V, 24 V and 48 V battery systems
- Adjustable voltage and hysteresis settings
- 1 x 5 A SPDT relay output

Voltage relays DUA55



- Voltage window relay
- Nominal voltage from 208 to 240 VAC
- Monitoring of own supply
- Incorrect connection proof (208-480 VAC power supply)
- 5 A SPDT relay output

Voltage relays DUB02/DUB03



- Over and undervoltage monitoring
- Measure own supply 24 V, 115 V, 230 VAC [DUB02], 24-240 VAC/DC [DUB03]
- Adjustable delay on alarm ON or on recovery
- Programmable latch / inhibit function
- 1 x 8 A SPDT output

Current/Voltage relays DIC01/DUC01



- TRMS AC or DC voltage monitoring
- Over + over or over + under or under + under
- Separately adjustable delays, adjustable hysteresis
- Programmable latch / inhibit function
- 2 x 8 A SPDT relay output

Thermistor relays DTA01/02, DTA71/72



- Motor thermistor relays for PTC connection
- Remote or local, automatic or manual alarm reset
- PTC open or short circuit information LED for status and troubleshooting
- 1 or 2 relays output

Thermistor relay DTA04



- Motor thermistor relays for PTC connection
- Remote or local, automatic or manual alarm reset
- PTC open or short circuit. Information LED for status and troubleshooting
- 2 x 8 A SPST relay output
- Relay outputs for contactor opening and signalling
- 24 V to 240 VAC/DC power supply voltage

Earth Leakage DEA71/DEB71



- Fixed [DEA71] or adjustable $I_{\Delta n}$ threshold [DEB71]
- Warning output @ 60% $I_{\Delta n}$
- Trip Output @ 80% $I_{\Delta n}$
- Adjustable time delay [DEB71]
- 2 SPDT relay outputs
- Sealable antitampering lid [DEB71]
- Works with CTG core balance transformers with openings from 35 mm to 210 mm

Frequency relays DFB01/DFC01



- Over and underfrequency monitoring
- Rated frequency 50 Hz or 60 Hz
- Adjustable delay on alarm ON or on recovery
- Programmable latch / inhibit function
- 1 x 8 A SPDT output [DFB01]
- 2 x 8 A SPDT output [DFC01]

Power relays DWA01/DWB



- Cos ϕ or Active power monitoring
- Direct reading up to 5 A, 10 A or through "MI" current transformers for higher currents
- Adjustable Cos ϕ or selectable independent upper and lower values
- Adjustable delay ON
- 1 x 8 A SPDT relay output

Pump alternating relays DLA71/DLA73



- For 2 or 3 pumps
- Pump rotation and multiple pumps activation
- Overflow relay output [DLA73]
- 2 x 5 A SPST relay output [DLA71 2P]
- 3 x 5 A SPST relay output [DLA71 3P, DLA73]

Timers

Timers are frequently used in a wide range of applications in automation, such as motor control centres, packaging machinery, HVAC equipment, control panels and process control systems. The Carlo Gavazzi timer portfolio is complete and offers solutions for different mountings (DIN-rail, panel or plug-in), functions (ON and OFF delay, interval, one-shot, recycler, star-delta) and output (SPDT, DPDT, 4PDT relay, or static output).

Delay on operation DAA/PAA	Delay on release DBA/PBA	True delay in release DBB/PBB	Star-delta DAC/PAC
-------------------------------	-----------------------------	----------------------------------	-----------------------



- Mini-DIN, DIN-rail or plug-in housing
- Time range 0.1 s to 100 h
- Universal power supply
- SPDT or DPDT relay output
- Approvals: CE - UL - CSA - RINA



- Mini-DIN, DIN-rail or plug-in housing
- Time range 0.1 s to 100 h
- Universal power supply
- SPDT relay output
- Approvals: CE - UL - CSA



- Mini-DIN, DIN-rail or plug-in housing
- Time range 0.1 s to 10 h
- Universal power supply
- SPDT or DPDT relay output
- Approvals: CE - UL - CSA



- Mini-DIN, DIN-rail or plug-in housing
- Time range 0.1 s to 600 s
- Universal power supply
- SPDT relay output
- Approvals: CE - UL - CSA

Recycler DCB/PCB	Multifunction DMB/PMB	Multifunction DMC/PMC	Multifunction FAA/FMB
---------------------	--------------------------	--------------------------	--------------------------



- Mini-DIN, DIN-rail or plug-in housing
- Time range 0.1 s to 100 h
- Universal power supply
- 1x or 2x SPDT relay output
- Approvals: CE - cULus



- Mini-DIN, DIN-rail or plug-in housing
- 7 functions (0.1 s to 100 h)
- Universal power supply
- 1x, 2x SPDT or DPDT output
- Approvals: CE - UL - CSA



- DIN-rail or plug-in housing
- 7 functions (0.1 s to 100 h)
- Remote time setting connections
- NPN, PNP, Namur sensors input
- 1x, 2x SPDT or DPDT output
- Approvals: CE - UL - CSA



- Panel or plug-in mounting
- 7 functions (0.02 s to 300 h)
- Universal power supply
- DPDT output
- Approvals: CE - UL - CSA

Multifunction HAA	Mini-E EAS/EBS/ECS
----------------------	-----------------------



- Plug-in mounting
- 4 functions (0.1 s to 100 h)
- Universal power supply
- DPDT or 4PDT output
- Approvals: CE - UL - CSA



- DIN-rail or panel mounting
- 3 functions (0.5 s to 10 m)
- Extended power supply
- Static output
- Approvals: CE - UL - CSA



OUR SALES NETWORK IN EUROPE

AUSTRIA

Carlo Gavazzi GmbH
Ketzergasse 374,
A-1230 Wien
Tel: +43 1 888 4112
Fax: +43 1 889 1053
office@carlogavazzi.at

BELGIUM

Carlo Gavazzi NV/SA
Mechelsesteenweg 311,
B-1800 Vilvoorde
Tel: +32 2 257 41 20
sales@carlogavazzi.be

DENMARK

Carlo Gavazzi Handel A/S
Over Hadstenvvej 40,
DK-8370 Hadsten
Tel: +45 89 60 61 00
Fax: +45 86 98 15 30
handel@gavazzi.dk

FINLAND

Carlo Gavazzi OY AB
Ahventie, 4 B
FI-02170 Espoo
Tel: +358 9 756 2000
myynti@gavazzi.fi

FRANCE

Carlo Gavazzi Sarl
Zac de Paris Nord II, 69, rue de la Belle Etoile,
F-95956 Roissy CDG Cedex
Tel: +33 1 49 38 98 60
Fax: +33 1 48 63 27 43
french.team@carlogavazzi.fr

GERMANY

Carlo Gavazzi GmbH
Pfnorstr. 10-14
D-64293 Darmstadt
Tel: +49 6151 81 00 0
Fax: +49 6151 81 00 40
info@gavazzi.de

GREAT BRITAIN

Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley, Surrey GU16 7SG
Tel: +44 1 276 854110
Fax: +44 1 276 682140
sales@carlogavazzi.co.uk

ITALY

Carlo Gavazzi SpA
Via Milano 13,
I-20045 Lainate
Tel: +39 02 931 76 1
Fax: +39 02 931 76 301
info@gavazziacbu.it

NETHERLANDS

Carlo Gavazzi BV
Wijkermeerweg 23,
NL-1948 NT Beverwijk
Tel: +31 251 22 93 45
Fax: +31 251 22 60 55
info@carlogavazzi.nl

NORWAY

Carlo Gavazzi AS
Melkeveien 13,
N-3919 Porsgrunn
Tel: +47 35 93 08 00
Fax: +47 35 93 08 01
post@gavazzi.no

PORTUGAL

Carlo Gavazzi Lda
Rua dos Jerónimos 38-B,
P-1400-212 Lisboa
Tel: +351 21 361 70 60
Fax: +351 21 362 13 73
carlogavazzi@carlogavazzi.pt

SPAIN

Carlo Gavazzi SA
Avda. Iparraguirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel: +34 94 480 40 37
Fax: +34 94 431 60 81
gavazzi@gavazzi.es

SWEDEN

Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel: +46 54 85 11 25
Fax: +46 54 85 11 77
info@carlogavazzi.se

SWITZERLAND

Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel: +41 41 747 45 35
Fax: +41 41 740 45 40
info@carlogavazzi.ch

OUR SALES NETWORK IN THE AMERICAS

USA

Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089-6904, USA
Tel: +1 847 465 61 00
Fax: +1 847 465 73 73
sales@carlogavazzi.com

CANADA

Carlo Gavazzi Inc.
2660 Meadowvale Boulevard,
Mississauga, ON L5N 6M6, Canada
Tel: +1 905 542 0979
Fax: +1 905 542 2248
gavazzi@carlogavazzi.com

MEXICO

Carlo Gavazzi Mexico S.A. de C.V.
Circuito Puericultores 22, Ciudad Satelite
Naucalpan de Juárez, Edo Mex. CP 53100
Mexico
T +52 55 5373 7042
F +52 55 5373 7042
mexicosales@carlogavazzi.com

BRAZIL

Carlo Gavazzi Automação Ltda.
Av. Francisco Matarazzo, 1752
Conj 2108 05001-200 - São Paulo - SP
Tel: +55 11 3052 0832
Fax: +55 11 3057 1753
info@carlogavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE

Carlo Gavazzi Automation Singapore Pte. Ltd.
61 Tai Seng Avenue #05-06
Print Media Hub @ Paya Lebar iPark
Singapore 534167
Tel: +65 67 466 990
Fax: +65 67 461 980
info@carlogavazzi.com.sg

MALAYSIA

Carlo Gavazzi Automation (M) SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46, 47301 - Petaling Jaya,
Selangor, Malaysia
Tel: +60 3 7842 7299
Fax: +60 3 7842 7399
info@gavazzi-asia.com

CHINA

Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1, 1002
Middle Shennan Zhong Road, Futian District,
Shenzhen, China
Tel: +86 755 8369 9500
Fax: +86 755 8369 9300
sales@carlogavazzi.cn

HONG KONG

Carlo Gavazzi Automation
Hong Kong Ltd.
Unit No. 16 on 25th Floor, One Midtown,
No. 11 Hoi Shing Road, Tsuen Wan,
New Territories, Hong Kong
Tel: +852 26261332 / 26261333
Fax: +852 26261316

TAIWAN

Branch of Carlo Gavazzi Automation
Singapore Pte. Ltd.
22F-1, No.500 Shizheng Rd, Xitun Dist,
Taichung City 407,
Taiwan, China
Tel: +886 4 2258 4001
Fax: +886 4 2258 4002

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK

Carlo Gavazzi Industri A/S
Hadsten

MALTA

Carlo Gavazzi Ltd
Zejtun

ITALY

Carlo Gavazzi Controls SpA
Belluno

LITHUANIA

Uab Carlo Gavazzi Industri Kaunas
Kaunas

CHINA

Carlo Gavazzi Automation (Kunshan) Co., Ltd.
Kunshan

HEADQUARTERS

Carlo Gavazzi Automation SpA
Via Milano, 13
I-20045 - Lainate (MI) - ITALY
Tel: +39 02 931 761
info@gavazziautomation.com



CARLO GAVAZZI
Automation Components

Energy to Components!

www.gavazziautomation.com



CAT PO ENG REV.24.11/21
Specifications are subject to change without notice. Illustrations are for example only.