


Measures without tolerance acc. to UNI ISO 2768-mk



TECHNICAL FEATURES AND POSSIBLE CONFIGURATIONS

- Max standard length....: 40,50,60 m
- Resolutions.....: 0,1 mm, 1 mm
- Output codes.....: Binary
- Weight.....: 18÷30kgacc. to the length
- Pullout cable force....: 25 N
- Pullin cable force....: 12 N
- Max acceleration.....: 2,5 G
- Max linearity error....: $\pm 0,05\%$ f.s.
- Max reading speed.....: 4 m/s
- Protection class....: encoder: IP64 mecc.: IP 64 (°)
output: see 'CONNECTION' page 2
- Power supply Vdc.....: 10÷30 Vdc
- Max consumption.....: 2,5 W
- Light source.....: LED with ≥ 100000 h life
- Optical sensors.....: Photodiodes ASIC
- Electronic output.....: Line driver (secondo RS485)
- Status indic. with 2 LEDs
- Output interface.....: (DP) Profibus-DP Class2
- Connect. : 3PG 3PG-VA 2M20
- For the codes and the descriptions of connectors see 'ORDERING CODE' on page 2.
- Average life.....: $>10^6$ cycles @ 2m/s
- Impact resistance.....: 30 G (11 ms)
- Vibration resistance...: 10 G (10 ÷ 1000 Hz)
- Operating temperature..: -20 ÷ +70 °C
- Storage temperature....: -40 ÷ +85 °C
- Humidity.....: 98% (without liquid state)
- Cable.....: $\emptyset$ 1,35 mm stainless steel
- Polarity inversion protect.
- Over voltage peak protect.
- Disc made of unbreakable and durable plastic.
- EMC certific. according to EN 61000-6-2, EN 61000-6-4

(°) IP according to CEI EN 60529, EN 60529, IEC 529

POSSIBLE OPTIONS

CODE	DESCRIPTION	CODE	DESCRIPTION	CODE	DESCRIPTION
P	Cable out.w.compressed air	U	Cable out. with 360° joint	X	Customer options
S	Lateral fixing bracket				



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
Phone: +39 011 715577/78 r.a.
MAIL: ELCIS s.r.l. P.O.Box 90 10093 COLLEGNO (TO) ITALY

* <http://www.elcis.com>
* e-mail: info@elcis.com
* Fax: +39 011 712613

