


PORTABLE ELECTRONIC HANDWHEEL

VP50

PORTABLE HANDWHEEL WITHOUT INSIDE ELECTRONIC COUNTER, MADE TO BE CONNECTED TO THE CNC THROUGH A SPIRAL CABLE. EXTREMELY STURDY EXECUTION WITH METAL HOUSING AND EMERGENCY MUSHROOM-HEAD PUSH BUTTON. POSSIBILITY OF MAGNETIC COUPLER AND DEAD-MAN-CONTROL.

Portable electr. handwheel
page: 02.VP50 1/2
data sheet IP 003 E00

Sized draw standard version: VD4
Measures without tolerance according to UNI ISO 2768-mk



VP50 is a portable handwheel to connect through a spiral cable to the CNC. The knob steps (100 PPR) have a detent at each division or upon request it is available clutched. A mushroom-head push button allows to immediately stop the machine tool. A handle (available upon request on right or left side) allows a steady hold of the handwheel. Upon request VP50 is available with a magnetic coupler for a steady fixing to the machine tool and a dead-man-control push button. Several operating voltages and output electronics allow to the handwheel of being interfaced with any CNC. VP50 is extremely sturdy thanks to his completely metallic housing. Good resistance to external agents.

TECHNICAL FEATURES AND POSSIBLE CONFIGURATIONS

- | | |
|--|---|
| <ul style="list-style-type: none"> - Housing.....: PAINTED ALUMINIUM - Knob/scale plate...: ANODIZED ALUMINIUM - Weight.....: 1350 g - Display.....: 100 DIV.ON KNOB'S FLANGE - Resolution.....: 100 DIV./REV. - IP output side.(°)..: see 'CONNECTIONS' of page 2 - IP shaft side.(°)..: 64 - Impact resistance..: 50 G x 11ms - Vibration strenght..: 12 G (10 ÷ 2000 Hz) - Starting torque Nm..: 0,12 | <ul style="list-style-type: none"> - Rotat. life @ 200 RPM: >= 1000000 h - Operating temperature: 0 ÷ 70 °C (*) - Storage temperature..: -30 ÷ 85 °C - Pulses per revolution: 100 - Max consumption mA...: std 120 line driver 180 - Light source.....: LED with >= 100000 h life - Connection.....: spiral cable 3 m long with cable end connector (see ORDERING INFO.). |
|--|---|

(°) IP according to CEI EN 60529, EN 60529, IEC 529

(*) custom options

ELECTRONICS

CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA	CODE	DESCRIPTION	mA
K	STANDARD NPN	10	N	DRIVER 26LS31	30						
Q	NPN OPEN COLL	10	C	DRIVER 88C30	20						
R	NPN	70									
P	NPN OPEN COLL	70									
U	PNP	70									
B	PNP OPEN COLL	70									
H	PUSH-PULL PRO	70									
	PUSH-PULL	70									

(S)

A

B

(S)

A

Ā

B

B̄

(S)

(S)

(S)

Tolerance between phases ± 25°, symmetry ± 15°

(S) Clock-wise output rotation (see shaft).




ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
Phone: +39 011 715577/78 a.r.
MAIL: ELCIS s.r.l. P.O.Box 90 10093 COLLEGNO (TO) ITALY

* <http://www.elcis.com>
* e-mail: info@elcis.com
* Fax: +39 011 712613

POSSIBLE OPTIONS				POSSIBLE CONNECTIONS			
CODE	DESCRIPTION	CODE	DESCRIPTION	CABLE		OUTPUT:	
F	Clutched						
E	Custom central logo			CONNECTOR		OUTPUT:	
K	Invert. phase A,B,Zero						
J	Right consent P.B.						
W	Left consent P.B.						
M	Magnetic coupler			CABLE END CONNECTOR		OUTPUT:	
D	Right handle			VD4 VM9 VM5 VL			
X	Custom options						
				TERMINAL BOX		OUTPUT:	

ORDERING INFORMATION



(1) For further informations see ELECTRONIC data sheet
(2) For further informations see CONNECTION data sheet

Product manufactured according to UNI EN ISO 9001:2000, supplied with CHECKING and CONFORMITY declaration with CE mark and with TWO (2) YEARS WARRANTY starting from delivery date.

ELCIS company has the right to make any changing without previous notice.

data sheet IP 003 E00 page: 02.VP50 2/2



ELCIS s.r.l. Via Rosa Luxembourg 12/14 10093 COLLEGNO (TO) ITALY
Phone: +39 011 715577/78 a.r.
MAIL: ELCIS s.r.l. P.O.Box 90 10093 COLLEGNO (TO) ITALY

* <http://www.elcis.com>
* e-mail: info@elcis.com
* Fax: +39 011 712613